



## Maxx® (Model 89076-4) Parts List

Parts shown in bold are optional accessories. Part categories and individual part listings are arranged alphabetically.

### Bearings & Bushings

5106A	Ball bearing, black rubber sealed (15x24x5mm) (2)
5107A	Ball bearing, black rubber sealed (17x26x5mm) (2)
5196A	Ball bearing, black rubber sealed (20x32x7mm) (2)
5099A	Ball bearing, black rubber sealed (6x16x5mm) (2)
2728	Ball bearings (5x8x2.5mm) (2)
5119A	Ball bearings, black rubber sealed (10x15x4mm) (2)
5120A	Ball bearings, black rubber sealed (12x18x4mm) (2)
5180A	Ball bearings, black rubber sealed (6x13x5mm) (2)
5101	Ball bearings, blue rubber sealed (12x21x5mm) (2)
7020	Ball bearings, blue rubber sealed (8x12x3.5mm) (2)

### Body & Accessories

8915	Body mounts, front & rear/ 3x12mm BCS (1)/ 3x12mm shoulder screw (2)/ 3x8mm CS (2)/ 3x15mm flat-head machine screw (9)
8910	Body reinforcement set, Maxx® (fits #8911 body)
8913	Body support, rear/ 3x10mm CS (4) (fits #8911 body)
<b>8911</b>	<b>Body, Maxx® (clear, untrimmed, requires painting)/ window masks/ decal sheet</b>
8911A	Body, Maxx®, blue (painted)/ decal sheet
8911T	Body, Maxx®, orange (painted)/ decal sheet
<b>8911X</b>	<b>Body, Maxx®, ProGraphix® (graphics are printed, requires paint &amp; final color application)/ decal sheet</b>
8911R	Body, Maxx®, red (painted)/ decal sheet
8917	Skid plate, roof (body) (black)/ 3x10mm CS (4)
<b>8917X</b>	<b>Skid plate, roof (body) (blue)/ 3x12mm CS (4)</b>
<b>8917G</b>	<b>Skid plate, roof (body) (green)/ 3x12mm CS (4)</b>
<b>8917T</b>	<b>Skid plate, roof (body) (orange)/ 3x12mm CS (4)</b>
<b>8917R</b>	<b>Skid plate, roof (body) (red)/ 3x12mm CS (4)</b>
<b>8917A</b>	<b>Skid plate, roof (body) (white)/ 3x12mm CS (4)</b>
<b>8912X</b>	<b>Tailgate protector, blue/ 3x15mm flat-head screw (4)</b>
<b>8912G</b>	<b>Tailgate protector, green/ 3x15mm flat-head screw (4)</b>
<b>8912T</b>	<b>Tailgate protector, orange/ 3x15mm flat-head screw (4)</b>
<b>8912R</b>	<b>Tailgate protector, red/ 3x15mm flat-head screw (4)</b>
<b>8912A</b>	<b>Tailgate protector, white/ 3x15mm flat-head screw (4)</b>
8912	Tailgate protector/ 3x15mm flat-head screw (4)

### Bumpers & Skidplates

8933	Bumper mount, front
8934	Bumper mount, rear
8935	Bumper, front
<b>8935X</b>	<b>Bumper, front (for use with #8990 LED light kit)</b>
8936	Bumper, rear
<b>8936X</b>	<b>Bumper, rear (for use with #8990 LED light kit)</b>
8945	Skidplate, center
8944	Skidplate, front (1), rear (1)

### Chassis & Attachments

8919	Battery hold-down/ mounts (front & rear)/ battery compartment spacers/ foam pads
8915	Body mounts, front & rear/ 3x12mm BCS (1)/ 3x12mm shoulder screw (2)/ 3x8mm CS (2)/ 3x15mm flat-head machine screw (9)
8924	Box, receiver (sealed)/ wire cover/ foam pads/ silicone grease/ 2.5x10 CS (2)/ 3x15 CCS (3)
8933	Bumper mount, front
8934	Bumper mount, rear
8935	Bumper, front
8936	Bumper, rear
8922	Chassis
8921	Chassis brace, front
8987	Covers, gear (2)
8923	Nerf bars, chassis (2)
8925	Seal kit, receiver box (includes o-ring, seals, and silicone grease)
8938	Shock tower, front (left & right halves)
8939	Shock tower, rear (left & right halves)
8945	Skidplate, center
8944	Skidplate, front (1), rear (1)
8976	Wheelie bar
<b>8976X</b>	<b>Wheelie bar, blue</b>
<b>8976G</b>	<b>Wheelie bar, green</b>
<b>8976T</b>	<b>Wheelie bar, orange</b>
<b>8976R</b>	<b>Wheelie bar, red</b>
<b>8976A</b>	<b>Wheelie bar, white</b>

### Cush Drive Components

6465	Cush drive key/ pin/ elastomer damper
7793X	Housing, cush drive (front & rear halves)

6447	Spur gear, 46-tooth (1.0 metric pitch)
<b>6447X</b>	<b>Spur gear, 46-tooth, steel (1.0 metric pitch)</b>
6448	Spur gear, 50-tooth (1.0 metric pitch)
<b>6448X</b>	<b>Spur gear, 50-tooth, steel (1.0 metric pitch)</b>
<b>6449</b>	<b>Spur gear, 54-tooth (1.0 metric pitch)</b>
<b>6449X</b>	<b>Spur gear, 54-tooth, steel (1.0 metric pitch)</b>

### Differential Components

8981	Carrier, differential/ x-ring gasket/ o-ring (2)/ 10x19.5x0.5 TW
<b>8980</b>	<b>Differential kit, center (complete)</b>
<b>5136X</b>	<b>Differential oil kit (1 each: 10K, 30K, 50K weights)</b>
8949	Differential output yoke assembly, front or rear (assembled with external-splined half shaft)
8982	Gear set, differential (output gears (2)/ spider gears (4)/ spider gear shaft (2)/ output shaft (2)/ 2.5x13.8 pin (2))
8988	Gear, center differential, 44-tooth
5041	Grease, premium high performance (20cc)
8985	Input gear, transmission, 22-tooth/ 2.5x12mm pin
8986	Input shaft, transmission
<b>5130</b>	<b>Oil, differential (100K weight) (.7 oz (20cc))</b>
<b>5135</b>	<b>Oil, differential (10K weight)</b>
5040	Oil, differential (20M weight) (standard)
5136	Oil, differential (30K weight)
8989	Output gear, center differential, hardened steel (2)
8978	Ring gear, differential/ pinion gear, differential (front)
8977	Ring gear, differential/ pinion gear, differential (rear)
8953	Stub axle assembly, outer (front or rear) (assembled with internal-splined half shaft)

### Driveline Components

8952	Carriers, stub axle (left & right)
8951	Drive cup (1)/ 4x15.8mm screw pin (use only with #8950 driveshaft)
8954	Drive hub, front (1)/ 3x10 screw pin (1)
8950	Driveshaft assembly, front or rear, Maxx® Duty (1) (left or right) (fully assembled, ready to install)/ screw pin (1)
8955	Driveshaft, center, aluminum
<b>8950X</b>	<b>Driveshaft, steel constant-velocity (shaft only, 89.5mm) (1) (for use only with #8951 drive cup)</b>
<b>8447A</b>	<b>Nuts, 5mm flanged nylon locking (aluminum, black-anodized, serrated) (4)</b>
<b>8447X</b>	<b>Nuts, 5mm flanged nylon locking (aluminum, blue-anodized, serrated) (4)</b>
<b>8447G</b>	<b>Nuts, 5mm flanged nylon locking (aluminum, green-anodized, serrated) (4)</b>
<b>8447R</b>	<b>Nuts, 5mm flanged nylon locking (aluminum, red-anodized, serrated) (4)</b>
8447	Nuts, 5mm flanged nylon locking (steel, black serrated) (8)
5040	Oil, differential (20M weight) (standard)
<b>8953</b>	<b>Stub axle assembly, outer (front or rear) (assembled with internal-splined half shaft)</b>
8956	Wheel hubs, hex (2)/ 2.5x12 pins (2)
<b>8956X</b>	<b>Wheel hubs, hex, aluminum (blue-anodized) (4)/ 4x13mm screw pins (4)</b>
<b>8957</b>	<b>Wheel washers, black (4)</b>
8957X	Wheel washers, blue (4)
<b>8957G</b>	<b>Wheel washers, green (4)</b>
<b>8957T</b>	<b>Wheel washers, orange (4)</b>
8957R	Wheel washers, red (4)

### Front Suspension & Steering

8926	Bulkhead tie bar, front, upper (1)/ lower (2) (steel)
8920	Bulkhead, front (upper and lower)
8932	Caster blocks (c-hubs), left & right
8916	Mount, tie bar, front (1)/ rear (1)/ suspension pin retainer, front or rear (2)
8947	Servo horn, steering/ linkage, steering (46mm, assembled with pivot balls)
8938	Shock tower, front (left & right halves)
8946	Steering bellcranks/ bellcrank support/ servo saver/ servo saver spring/ draglink/ 3x20mm shoulder screws (2)
8937	Steering blocks, left & right
8930	Suspension arm, lower, black (left or right, front or rear) (2)
<b>8930X</b>	<b>Suspension arm, lower, blue (left and right, front or rear) (2)</b>
<b>8930G</b>	<b>Suspension arm, lower, green (left and right, front or rear) (2)</b>
<b>8930T</b>	<b>Suspension arm, lower, orange (left and right, front or rear) (2)</b>
<b>8930R</b>	<b>Suspension arm, lower, red (left and right, front or rear) (2)</b>
<b>8930A</b>	<b>Suspension arm, lower, white (left and right, front or rear) (2)</b>
8929	Suspension arms, upper, black (left or right, front or rear) (2)

## Page 2 Maxx®: TQi Traxxas Link Enabled 2.4GHz Radio & TSM (Model 89076-4) Parts List

8929X	Suspension arms, upper, blue (left or right, front or rear) (2)
8929G	Suspension arms, upper, green (left or right, front or rear) (2)
8929T	Suspension arms, upper, orange (left or right, front or rear) (2)
8929R	Suspension arms, upper, red (left or right, front or rear) (2)
8929A	Suspension arms, upper, white (left or right, front or rear) (2)
8941	Suspension pins, lower, inner (front or rear), 4x64mm (2) (hardened steel)
8940	Suspension screw pin set, front or rear (hardened steel), 4x18mm (4), 4x38mm (2), 4x33mm (2), 4x43mm (2)

### Hardware

3642	Attachment screws, shock (3x12mm shoulder screws) (6)
1552	Backplate screws (3x8mm cap-head machine) (6)/washers (6)/wrench
2584	Head screws, 3x12mm cap-head machine (hex drive) (6) (TRX 2.5, 2.5R, 3.3)
8447A	Nuts, 5mm flanged nylon locking (aluminum, black-anodized, serrated) (4)
8447X	Nuts, 5mm flanged nylon locking (aluminum, blue-anodized, serrated) (4)
8447G	Nuts, 5mm flanged nylon locking (aluminum, green-anodized, serrated) (4)
8447R	Nuts, 5mm flanged nylon locking (aluminum, red-anodized, serrated) (4)
8447	Nuts, 5mm flanged nylon locking (steel, black serrated) (8)
5147X	Nuts, 5mm flanged nylon locking (steel, serrated) (8)
3236	Screws, 2.5x12mm cap-head machine (6)
2577	Screws, 3x10mm button-head machine (hex drive) (6)
2587	Screws, 3x10mm cap-head machine (6) (no washer)
2551	Screws, 3x10mm countersunk machine (6) (hex drive)
4859	Screws, 3x10mm flat-head machine (hex drive) (4)
2578	Screws, 3x12mm button-head machine (hex drive) (6)
2579	Screws, 3x15mm button-head machine (hex drive) (6)
2553	Screws, 3x15mm countersunk machine (6) (hex drive)
3646	Screws, 3x15mm flat-head machine (hex drive) (6)
2583	Screws, 3x18mm button-head machine (hex drive) (6)
2581	Screws, 3x25mm button-head machine (hex drive) (6)
2582	Screws, 3x30mm button-head machine (hex drive) (6)
2550	Screws, 3x8mm countersunk machine (6) (hex drive)
3936	Screws, 4x10mm button-head machine (hex drive) (6)
2535	Screws, 4x10mm countersunk machine (hex drive) (6)
3937	Screws, 4x12mm button-head machine (hex drive) (6)
3938	Screws, 4x14mm button-head machine (hex drive) (6)
3933	Screws, 4x16mm button-head machine (hex drive) (6)
2589	Screws, 4x20mm button-head machine (hex drive) (6)
2596	Screws, 4x25mm button-head machine (hex drive) (6)
2595	Screws, 4x35mm button-head machine (hex drive) (6)

### Motors & Electronics

3463	Cooling fan kit (with shroud), Velineon 540XL motor
3475	Cooling fan, Velineon® VXL ESC (fits VXL-6s & VXL-8s)
8987	Covers, gear (2)
2092	Gear set (for 2090 servo)
3462	Heat sink, Velineon 540XL motor
8960	Motor mounts (front and rear)/ pin (1)
3461	Motor, Velineon 540XL, 2400Kv 70mm, brushless (assembled with 12-gauge wire and gold-plated bullet connectors) (for Maxx®)
3464	Mount, motor cooling fan (fits #3461 motor)
2091	Servo case/ gaskets (for 2090 waterproof servo)
2090	Servo, digital high-torque (ball bearing), waterproof
3465	Velineon® VXL-4s Electronic Speed Control, waterproof (brushless) (fwd/rev/brake)

### Radio System, Batteries & Chargers

2849X	4000mAh 11.1v 3-Cell 25C LiPo Battery
2872X	5000mAh 11.1v 3-Cell 25C LiPo Battery
2888X	5000mAh 14.8v 4-Cell 25C LiPo Battery
2889X	5000mAh 14.8v 4-Cell 25C LiPo Battery
2857X	6400mAh 11.1v 3-Cell 25C LiPo Battery
2878X	8400mAh 11.1v 3-Cell 25C LiPo Battery
2938X	Adapter, Traxxas® iD® LiPo battery (adapts Traxxas iD batteries to separate balance ports)
1926	Antenna caps, vinyl (2)/ antenna spool
1726	Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1)
1726A	Antenna, tube, black (1)/ vinyl antenna cap (1)/ wire retainer (1)
2943	Battery charge indicators (green (4), blue (4), grey (4))
6548	Battery door, transmitter (replacement for #6516, 6517, 6528, 6529, 6530 transmitters)
2914	Battery, Power Cell AA Alkaline (4)
2990	Battery/charger complete pack (includes #2972 Dual iD® charger (1), #2872X 5000mAh 11.1V 3-cell 25C LiPo battery (2))
2972	Charger, EZ-Peak® Dual, 100W, NiMH/LiPo with iD® Auto Battery Identification

2973	Charger, EZ-Peak® Live Dual, 200W, NiMH/LiPo with iD® Auto Battery Identification
2971	Charger, EZ-Peak® Live, 100W, NiMH/LiPo with iD® Auto Battery Identification
2970	Charger, EZ-Peak® Plus, 4 amp, NiMH/LiPo with iD® Auto Battery Identification
6525	Communication link, telemetry expander
2092	Gear set (for 2090 servo)
2968X	LiPo cell voltage checker/balancer (includes #2938X adapter for Traxxas® iD® batteries)
2968	LiPo cell voltage checker/balancer (requires #2938X adapter for Traxxas® iD® batteries)
6533	Receiver, micro, TQi 2.4GHz with telemetry & TSM (5-channel)
6552	Seal kit, expander box (includes o-ring, seals, and silicone grease)
6526	Sensor, auto-detectable, temperature
6527	Sensor, auto-detectable, voltage
6521	Sensor, temperature and voltage (long)
2091	Servo case/ gaskets (for 2090 waterproof servo)
2090	Servo, digital high-torque (ball bearing), waterproof
6553X	Telemetry expander 2.0 and GPS module 2.0, TQi radio system
6550X	Telemetry expander 2.0, TQi radio system (compatible only with #6551X GPS module)
6551X	Telemetry GPS module 2.0, TQi radio system (compatible only with #6550X telemetry expander)
6509R	TQi 2.4 GHz High Output radio system, 2-channel, Traxxas Link™ enabled, TSM (2-ch transmitter, 5-ch micro receiver)
6507R	TQi 2.4 GHz High Output radio system, 4-channel with Traxxas Link™ Wireless Module, TSM (4-ch transmitter, 5-ch micro receiver)
6528	Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 2-channel (transmitter only)
6529	Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 3-channel (transmitter only)
6530	Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 4-channel (transmitter only)
6511	Traxxas Link™ Wireless Module

### Ready-To-Race Model

89076-4	Maxx®: 1/10 Scale 4WD Brushless Electric Monster Truck with TQi Traxxas Link™ Enabled 2.4GHz Radio System & Traxxas Stability Management (TSM)®
---------	---

### Rear Suspension

8927	Bulkhead tie bar, rear, upper (1)/ lower front (1)/ lower rear (1) (steel)
8928	Bulkhead, rear (upper and lower)
8952	Carriers, stub axle (left & right)
8916	Mount, tie bar, front (1)/ rear (1)/ suspension pin retainer, front or rear (2)
8939	Shock tower, rear (left & right halves)
8930	Suspension arm, lower, black (left or right, front or rear) (2)
8930X	Suspension arm, lower, blue (left and right, front or rear) (2)
8930G	Suspension arm, lower, green (left and right, front or rear) (2)
8930T	Suspension arm, lower, orange (left and right, front or rear) (2)
8930R	Suspension arm, lower, red (left and right, front or rear) (2)
8930A	Suspension arm, lower, white (left and right, front or rear) (2)
8929	Suspension arms, upper, black (left or right, front or rear) (2)
8929X	Suspension arms, upper, blue (left or right, front or rear) (2)
8929G	Suspension arms, upper, green (left or right, front or rear) (2)
8929T	Suspension arms, upper, orange (left or right, front or rear) (2)
8929R	Suspension arms, upper, red (left or right, front or rear) (2)
8929A	Suspension arms, upper, white (left or right, front or rear) (2)
8941	Suspension pins, lower, inner (front or rear), 4x64mm (2) (hardened steel)
8940	Suspension screw pin set, front or rear (hardened steel), 4x18mm (4), 4x38mm (2), 4x33mm (2), 4x43mm (2)

### Shocks (GT-Maxx®)

8965X	Body, GT-Maxx® shock (aluminum, blue-anodized) (1)
8965G	Body, GT-Maxx® shock (aluminum, green-anodized) (1)
8965T	Body, GT-Maxx® shock (aluminum, orange-anodized) (1)
8965R	Body, GT-Maxx® shock (aluminum, red-anodized) (1)
8962	Rebuild kit, GT-Maxx® shocks (lower cartridge, assembled, pistons, piston nuts, bladders) (renews 2 shocks)
8964X	Shock caps, aluminum (blue-anodized), GT-Maxx® shocks (4)
8964G	Shock caps, aluminum (green-anodized), GT-Maxx® shocks (4)
8964T	Shock caps, aluminum (orange-anodized), GT-Maxx® shocks (4)
8964R	Shock caps, aluminum (red-anodized), GT-Maxx® shocks (4)
8964	Shock caps, GT-Maxx® shocks/ spring perch/ adjusters/ 2.5x14 CS (2) (for 2 shocks)
8963	Shock shaft, 72mm (GT-Maxx®) (steel, chrome finish) (2)
8961	Shocks, GT-Maxx®, aluminum (blue-anodized) (fully assembled w/o springs) (2)

8961R	Shocks, GT-Maxx®, aluminum (red-anodized) (fully assembled w/o springs) (2)
1667	Silicone shock oil (30 wt), 60cc
8968X	Spring retainer (adjuster), blue-anodized aluminum, GT-Maxx® shocks (4) (assembled with o-ring)
8968G	Spring retainer (adjuster), green-anodized aluminum, GT-Maxx® shocks (4) (assembled with o-ring)
8968R	Spring retainer (adjuster), red-anodized aluminum, GT-Maxx® shocks (4) (assembled with o-ring)
8966	Springs, shock (natural finish) (GT-Maxx®) (1.210 rate) (2)
8967	Springs, shock (natural finish) (GT-Maxx®) (1.450 rate) (2)

### Spur Gears & Pinion Gears

6487X	Gear, 15-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw (compatible with steel spur gears)
6489X	Gear, 16-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw (compatible with steel spur gears)
6490X	Gear, 17-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw (compatible with steel spur gears)
6491X	Gear, 18-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw (compatible with steel spur gears)
6494X	Gear, 20-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw (compatible with steel spur gears)
6495X	Gear, 22-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw (compatible with steel spur gears)
6496X	Gear, 24-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw (compatible with steel spur gears)
6447	Spur gear, 46-tooth (1.0 metric pitch)
6447X	Spur gear, 46-tooth, steel (1.0 metric pitch)
6448	Spur gear, 50-tooth (1.0 metric pitch)
6448X	Spur gear, 50-tooth, steel (1.0 metric pitch)
6449	Spur gear, 54-tooth (1.0 metric pitch)
6449X	Spur gear, 54-tooth, steel (1.0 metric pitch)

### Steering Components

2728	Ball bearings (5x8x2.5mm) (2)
7020	Ball bearings, blue rubber sealed (8x12x3.5mm) (2)
8947	Servo horn, steering/ linkage, steering (46mm, assembled with pivot balls)
8946	Steering bellcranks/ bellcrank support/ servo saver/ servo saver spring/ draglink/ 3x20mm shoulder screws (2)
8948	Toe links, molded composite, 100mm (89mm center to center) (black) (2)

### Suspension Linkage

8941	Suspension pins, lower, inner (front or rear), 4x64mm (2) (hardened steel)
8940	Suspension screw pin set, front or rear (hardened steel), 4x18mm (4), 4x38mm (2), 4x33mm (2), 4x43mm (2)
8948	Toe links, molded composite, 100mm (89mm center to center) (black) (2)

### Team Traxxas Items

2514	Decal sheet, racing sponsors
9950	Official Team Traxxas® racing decal set (flag logo/ 6-color)
9909	Traxxas® racing banner, red & black (3x7 feet)

### Tires & Wheels

8447A	Nuts, 5mm flanged nylon locking (aluminum, black-anodized, serrated) (4)
8447X	Nuts, 5mm flanged nylon locking (aluminum, blue-anodized, serrated) (4)
8447G	Nuts, 5mm flanged nylon locking (aluminum, green-anodized, serrated) (4)
8447R	Nuts, 5mm flanged nylon locking (aluminum, red-anodized, serrated) (4)
8447	Nuts, 5mm flanged nylon locking (steel, black serrated) (8)
5147X	Nuts, 5mm flanged nylon locking (steel, serrated) (8)
8972	Tires & wheels, assembled, glued (black wheels, Maxx® All-Terrain tires, foam inserts) (2) (17mm splined) (TSM® rated)
8970	Tires, Maxx® All-Terrain 2.8" (2)/ foam inserts (2)
8956	Wheel hubs, hex (2)/ 2.5x12 pins (2)
8956X	Wheel hubs, hex, aluminum (blue-anodized) (4)/ 4x13mm screw pins (4)
8957	Wheel washers, black (4)
8957X	Wheel washers, blue (4)
8957G	Wheel washers, green (4)
8957T	Wheel washers, orange (4)
8957R	Wheel washers, red (4)
8971	Wheels (black) (2)

### Transmission Components

8987	Covers, gear (2)
8985	Input gear, transmission, 22-tooth/ 2.5x12mm pin
8986	Input shaft, transmission
5040	Oil, differential (20M weight) (standard)

### Traxxas Tools

3433X	Body reamer (aluminum handle)
3433	Body reamer (plastic handle)
3436	Cap, body reamer
3432	Scissors, curved tip
3431	Scissors, straight tip
8712	Speed Bit Essentials Set, hex and nut driver, 7-piece, includes premium handle (medium), travel pouch, hex drivers (straight: 1.5mm, 2.0mm, 2.5mm) and nut drivers (5.0mm, 5.5mm, 7.0mm, and 8.0mm), 1/4" drive
8721	Speed bit handle, medium (one piece)
8720	Speed bit handle, premium, large (rubber overmold)
8722	Speed bit handle, premium, medium (rubber overmold)
8710	Speed Bit Master Set, hex and nut driver, 13-piece, includes premium handle (medium), travel pouch, hex drivers (straight: 1.5mm, 2.0mm, 2.5mm, 3.0mm), (ball-end: 2.0mm, 2.5mm, 3.0mm), and nut drivers (4.0mm, 4.5mm, 5.0mm, 5.5mm, 7.00mm, 8.00mm),
8711	Speed Bit Master Set, hex driver, 7-piece straight and ball end, includes premium handle (medium), travel pouch, hex drivers (straight: 1.5mm, 2.0mm, 2.5mm, 3.0mm) (ball end: 2.0mm, 2.5mm, 3.0mm), 1/4" drive
8719	Speed Bit Master Set, nut driver, 6-piece, includes premium handle (medium), travel pouch, and nut drivers (4.0mm, 4.5mm, 5.0mm, 5.5mm, 7.0mm, 8.0mm), 1/4" drive
8716	Speed Bit Set, hex driver, 2-piece ball-end (2.0mm, 2.5mm), 1/4" drive
8716X	Speed Bit Set, hex driver, 3-piece ball-end (2.0mm, 2.5mm, 3.0mm), 1/4" drive
8715	Speed Bit Set, hex driver, 3-piece straight (1.5mm, 2.0mm, 2.5mm), 1/4" drive
8715X	Speed Bit Set, hex driver, 4-piece straight (1.5mm, 2.0mm, 2.5mm, 3.0mm), 1/4" drive
3415	Tool set with pouch (includes 1.5mm, 2.0mm, 2.5mm, 3.0mm, 3.5mm, 4mm drivers/ 4mm, 5mm, 5.5mm, 7mm and 8mm nut drivers/ 2mm, 4mm, and 5mm slotted screwdrivers/ #00 Phillips, #0 Phillips, and #1 Phillips screwdrivers/ 4mm and 8mm wrench/ driver handle

### Turnbuckles & Threaded Rods

8948	Toe links, molded composite, 100mm (89mm center to center) (black) (2)
------	--

If you have questions or need technical assistance, call Traxxas at:

**1-888-TRAXXAS**

(1-888-872-9927) (U.S. residents only)

For orders, calls outside the U.S., and other information, call 972-549-3000, or fax to 972-549-3011 e-mail Traxxas at support@Traxxas.com

**TRAXXAS.COM**