

X-Maxx® (Model 77086-4) Parts List

Parts shown in bold are optional accessories. Part categories and individual part listings are arranged alphabetically.

	Bearings & Bushings	6447R	Spur gear, 46-tooth, steel (wide-face, 1.0 metric pitch)
5106A	Ball bearing, black rubber sealed (15x24x5mm) (2)	6448R	Spur gear, 50-tooth, steel (wide-face, 1.0 metric pitch)
5108A	Ball bearing, black rubber sealed (15x26x5mm) (2)	6449X	Spur gear, 54-tooth, steel (1.0 metric pitch)
5107A	Ball bearing, black rubber sealed (17x26x5mm) (2)	6449R	Spur gear, 54-tooth, steel (wide-face, 1.0 metric pitch)
5196A	Ball bearing, black rubber sealed (20x32x7mm) (2)		Differential Components
5106	Ball bearing, blue rubber sealed (15x24x5mm) (2)	7781X	Carrier, differential (aluminum) (requires #7783X spider gear shaft)
4611	Ball bearings (5x11x4mm) (2)	7781	Carrier, differential/ x-ring gaskets (2)/ ring gear gasket/ 6x10x0.5 TW
5120A	Ball bearings, black rubber sealed (12x18x4mm) (2)	5136X	Differential oil kit (50cc of 1 each: 10K, 30K, 50K weights)
5180A	Ball bearings, black rubber sealed (6x13x5mm) (2)	7880	Differential, front, complete (fits X-Maxx® 8s)
5119	Ball bearings, blue rubber sealed (10x15x4mm) (2)	7881	Differential, rear, complete (fits X-Maxx® 8s)
5116	Ball bearings, blue rubber sealed (5x11x4mm) (2)	7782	Gear set, differential (output gears (2)/ spider gears (4)/
	Body & Accessories	5041	16x23.5x.5mm TW (2)) Grease, premium high performance (20cc)
7715	Body mounts, front & rear/3x15mm BCS (1)/ 3x12mm shoulder screw	7780	Housing, differential (front/rear)
	(2)/ 3x10mm flat-head machine screw (6)/ 3x15mm flat-head machine	5040	Oil, differential (20M wt) (standard)
	screw (2)	7790	Pinion gear, differential, 11-tooth (front) (heavy duty) (use with #7792
7710	Body reinforcement set (fits #7711 body)		35-tooth differential ring gear)
7713X	Body support, rear/ 3x15mm CS (2) / 3x15mm flat-head machine (2)	7791	Pinion gear, differential, 11-tooth (rear) (heavy duty) (use with #7792
7711	(fits X-Maxx®) Body, X-Maxx® (clear, trimmed, requires painting)/ window		35-tooth differential ring gear)
//!!	masks/ decal sheet	7792	Ring gear, differential, 35-tooth (heavy duty) (use with #7790, #7791
7811G	Body, X-Maxx®, green (painted, decals applied) (assembled with		11-tooth differential pinion gears)
70110	front & rear body mounts, rear body support, and tailgate protector)	7783	Spider gear shaft (2)/ spacers (4)/ 16x23.5x.5mm TW (2)
7811	Body, X-Maxx®, orange (painted, decals applied) (assembled with	7783X	Spider gear shaft (2)/ spacers (4)/16x23.5x.5 stainless washer (2) (for #7781X aluminum differential carrier)
	front & rear body mounts, rear body support, and tailgate protector)		,
7711X	Body, X-Maxx®, ProGraphix® (graphics are printed, requires		Driveline Components
	paint & final color application)/ decal sheet	7794	Cush drive key/ pin/ elastomer damper
7811R	Body, X-Maxx®, red (painted, decals applied) (assembled with front &	7754X	Drive cup (1)/ 3x8mm CS (for use only with #7750X driveshaft)
7744T	rear body mounts, rear body support, and tailgate protector)	7755	Driveshaft assembly, center, aluminum
7711T	Body, X-Maxx®, Rock n' Roll (painted, decals applied) (assembled with tailgate protector)	7750X	Driveshaft, steel constant-velocity (heavy duty, shaft only, 160mm) (1)
7817	Skid plate, roof (body) (black)/ 3x15mm CS (4) (requires #7713X		(replacing #7750 also requires #7751X, #7754X and #7768, 7768A,
	to mount)	5040	7768G, 7768R, or 7768T) Oil, differential (20M wt) (standard)
7817X	Skid plate, roof (body) (blue)/ 3x15mm CS (4) (requires #7713X	7751X	Rebuild kit, steel constant-velocity driveshaft (includes pins for 2
	to mount)	11317	driveshaft assemblies (for use only with #7750X driveshaft)
7817G	Skid plate, roof (body) (green)/ 3x15mm CS (4) (requires #7713X	7737X	Steering blocks, left & right (require 20x32x7 ball bearings)
	to mount)	7768A	Stub axle, aluminum (black-anodized) (1) (for use only with
7817T	Skid plate, roof (body) (orange)/ 3x15mm CS (4) (requires #7713X		#7750X driveshaft)
7047D	to mount)	7768	Stub axle, aluminum (blue-anodized) (1) (for use only with #7750X
7817R	Skid plate, roof (body) (red)/ 3x15mm CS (4) (requires #7713X to mount)		driveshaft)
7817A	Skid plate, roof (body) (white)/ 3x15mm CS (4) (requires #7713X	7768G	Stub axle, aluminum (green-anodized) (1) (for use only with #7750X
. •	to mount)	7768R	driveshaft) Stub axle, aluminum (red-anodized) (1) (for use only with #7750X
7712	Tailgate protector/ 3x8mm flat-head screw (4)	77001	driveshaft)
	Bumpers & Skidplates	7768T	Stub axle, aluminum, (orange-anodized) (1) (for use only with #7750X
7733	Bumper mount, front/ bumper support		driveshaft)
7734	Bumper mount, rear/ bumper support	7758A	Wheel nuts, splined, 17mm, serrated (black-anodized) (4)
7735	Bumper, front	7758	Wheel nuts, splined, 17mm, serrated (blue-anodized) (4)
7736	Bumper, rear	7758G	Wheel nuts, splined, 17mm, serrated (green-anodized) (4)
7745	Skidplate, center	7758T	Wheel nuts, splined, 17mm, serrated (orange-anodized) (4)
7744	Skidplate, front (1), rear (1)/ rubber impact cushion (2)	7758R	Wheel nuts, splined, 17mm, serrated (red-anodized) (4)
	Chassis & Attachments		Front Suspension & Steering
		7726	Bulkhead tie bar, upper (1)/ lower (2) (steel)
7719 7710	Battery hold-down (2)/ foam pad (2)	7721	Bulkhead, front (lower)
7718 7715	Battery hold-down mounts, left (2)/ right (2)/ 3x18mm CS (4)	7720	Bulkhead, front (upper)
7715	Body mounts, front & rear/3x15mm BCS (1)/ 3x12mm shoulder screw (2)/ 3x10mm flat-head machine screw (6)/ 3x15mm flat-head machine	7732	Caster blocks (c-hubs), left & right
	screw (2)	7716	Mount, tie bar, front (1)/ rear (1)
7724	Box, receiver (sealed)/ wire cover/ foam pads/ silicone grease/ 3x15	7747	Servo horn, steering/ linkage, steering (46mm, assembled with pivot
	CS (4)		balls)
7733	Bumper mount, front/ bumper support	7739	Shock tower, front (left & right halves)
7734	Bumper mount, rear/ bumper support	7746	Steering bellcranks/ bellcrank support/servo saver/ servo saver
7735	Bumper, front	7707	spring/ draglink/ 3x20mm shoulder screws (2)
7736	Bumper, rear	7737X 7746X	Steering blocks, left & right (require 20x32x7 ball bearings) Steering link, steel/ servo saver spring, heavy duty (use with
7722	Chassis	11401	#2085X metal gear servo)
7714X	Chassis top brace	7831	Suspension arm, black, lower (left, front or rear), heavy duty (1)
7723	Nerf bars, chassis (2)	7830	Suspension arm, black, lower (right, front or rear), heavy duty (1)
7725 7745	Seal kit, receiver box (includes o-ring, seals, and silicone grease)	7829	Suspension arm, black, upper (left or right, front or rear), heavy
7745 7744	Skidplate, center Skidplate, front (1) rear (1)/ rubber impost sushion (2)		duty (2)
7744 7717×	Skidplate, front (1), rear (1)/ rubber impact cushion (2)	7831X	Suspension arm, blue, lower (left, front or rear), heavy duty (1)
7717X 7776	Spacer, battery compartment (2)/ foam blocks (4)/ foam pad (2)	7830X	Suspension arm, blue, lower (right, front or rear), heavy duty (1)
7776 7775	Wheelie bar, black (assembled) Wheels (2) (for #7776 or #8976 wheelie bar)	7831G	Suspension arm, green, lower (left, front or rear), heavy duty (1)
		7830G	Suspension arm, green, lower (right, front or rear), heavy duty
	Cush Drive Components		(1)
7794 7793X	Cush drive key/ pin/ elastomer damper Housing, cush drive (front & rear halves)	7831T	Suspension arm, orange, lower (left, front or rear), heavy duty (1)

Page 2	X-Maxx®: TQi™ Traxxas Link™ Enabled 2.4GHz Ra	adio & T	SM® (Model 77086-4) Parts List
7830T	Suspension arm, orange, lower (right, front or rear), heavy duty (1)	2085	Servo, digital high-torque (ball bearing), waterproof (X-Maxx®/Maxx® mount)
7831R	Suspension arm, red, lower (left, front or rear), heavy duty (1)	2085X	Servo, digital high-torque, metal gear (ball bearing), waterproof/
7830R	Suspension arm, red, lower (right, front or rear), heavy duty (1)	2400	servo saver spring/ steering link
7831A 7830A	Suspension arm, white, lower (left, front or rear), heavy duty (1)	3496	Velineon® VXL-8s Electronic Speed Control, waterproof (brushless) (fwd/rev/brake)
7829X	Suspension arm, white, lower (right, front or rear), heavy duty (1) Suspension arms, blue, upper (left or right, front or rear), heavy duty (2)	7759	Washers, motor mount, aluminum (blue-anodized) (4)/ 4x18mm BCS (4)
7829G	Suspension arms, green, upper (left or right, front or rear), heavy duty (2)	7759G	Washers, motor mount, aluminum (green-anodized) (4)/ 4x18mm BCS (4)
7731	Suspension arms, lower (left, front or rear) (1)	7759R	Washers, motor mount, aluminum (red-anodized) (4)/ 4x18mm
7730	Suspension arms, lower (right, front or rear) (1)		BCS (4)
7829T	Suspension arms, orange, upper (left or right, front or rear), heavy duty (2)	20707	Radio System, Batteries & Chargers
7829R	Suspension arms, red, upper (left or right, front or rear), heavy duty (2)	2872X 2889X	5000mAh 11.1v 3-Cell 25C LiPo Battery 5000mAh 14.8v 4-Cell 25C LiPo Battery
7729	Suspension arms, upper (left or right, front or rear) (2)	2857X 2890X	6400mAh 11.1v 3-Cell 25C LiPo Battery 6700mAh 14.8v 4-Cell 25C LiPo Battery
7829A	Suspension arms, white, upper (left or right, front or rear), heavy duty (2)	2938X	Adapter, Traxxas® iD® LiPo battery (adapts Traxxas iD batteries to separate balance ports)
7743 7740	Suspension pin retainer (4)	2943	Battery charge indicators (green (4), blue (4), gray (4))
7740	Suspension pin set, front or rear corner (hardened steel), 4x85mm (1), 4x47mm (3), 4x33mm (2) (qty 4, #7740 required for complete set)	6548	Battery door, transmitter (replacement for #6516, 6517, 6528, 6529,
7742	Suspension pin set, shock mount (front or rear, hardened steel),	0044	6530 transmitters)
	4x25mm (2), 4x38mm (2)	2914 2990	Battery, Power Cell AA Alkaline (4) Battery/charger completer pack (includes #2972 Dual iD®
7741	Suspension pins, 4x85mm (hardened steel) (2)	2990	charger (1), #2872X 5000mAh 11.1V 3-cell 25C LiPo battery (2))
	Hardware	2997	Battery/charger completer pack (includes #2973 Dual iD charger
2585 2584	Cylinder head bolts, marine 3x20mm CS (6) (TRX 2.5) Head screws, 3x12mm cap-head machine (hex drive) (6) (TRX 2.5,	2972	(1), #2890X 6700mAh 14.8V 4-cell 25C LiPo battery (2)) Charger, EZ-Peak® Dual, 100W, NiMH/LiPo with iD® Auto Battery
	2.5R, 3.3)	0070	Identification
2586 4955	Head screws, 3x15mm cap-head machine (hex drive) (6) (TRX 2.5) Pins, axle (2.5x12mm) (4)	2973	Charger, EZ-Peak® Live Dual, 200W, NiMH/LiPo with iD® Auto Battery Identification
3234 2577	Screws, 2.5x14mm cap-head machine (hex drive) (6)	2971	Charger, EZ-Peak® Live, 100W, NiMH/LiPo with iD® Auto Battery Identification
2587	Screws, 3x10mm button-head machine (hex drive) (6) Screws, 3x10mm cap-head machine (6) (no washer)	2981	Charger, EZ-Peak® Plus 4s, 8 amp, NiMH/LiPo with iD® Auto Battery Identification
4859 2593	Screws, 3x10mm flat-head machine (hex drive) (4) Screws, 3x14mm button-head machine (hex drive) (6)	2970	Charger, EZ-Peak® Plus, 4 amp, NiMH/LiPo with iD® Auto
2579	Screws, 3x14mm button-head machine (hex drive) (6)		Battery Identification
3646	Screws, 3x15mm flat-head machine (hex drive) (6)	6525	Communication link, telemetry expander
4857	Screws, 3x20mm countersunk machine (hex drive) (6)	2087 2087X	Gear set (for 2085 servo) Gear set, metal (for 2085 & 2085X servos)
2581	Screws, 3x25mm button-head machine (hex drive) (6)	2968X	LiPo cell voltage checker/balancer (includes #2938X adapter for
2575	Screws, 3x6mm button-head machine (hex drive) (6)	2000%	Traxxas® iD® batteries)
2576 2535	Screws, 3x8mm button-head machine (hex drive) (6) Screws, 4x10mm countersunk machine (hex drive) (6)	2968	LiPo cell voltage checker/balancer (requires #2938X adapter for
3937	Screws, 4x12mm button-head machine (hex drive) (6)	6533	Traxxas® iD® batteries) Receiver, micro, TQi 2.4GHz with telemetry & TSM (5-channel)
3938	Screws, 4x14mm button-head machine (hex drive) (6)	6552	Seal kit, expander box (includes o-ring, seals, and silicone
2594	Screws, 4x15mm button-head machine (hex drive) (6)	0002	grease)
2546	Screws, 4x15mm countersunk machine (hex drive) (6)	6526	Sensor, auto-detectable, temperature
3933 2597	Screws, 4x16mm button-head machine (hex drive) (6) Screws, 4x22mm button-head machine (hex drive) (6)	6527	Sensor, auto-detectable, voltage
2596	Screws, 4x25mm button-head machine (hex drive) (6)	6531 6534	Sensor, temperature & voltage (fits X-Maxx®)
2598X	Screws, 4x30mm button-head machine (hex drive) (6)	6521 2086	Sensor, temperature and voltage (long) Servo case/gaskets (for 2085 & 2085X servos)
2595	Screws, 4x35mm button-head machine (hex drive) (6)	2085	Servo, digital high-torque (ball bearing), waterproof (X-Maxx®/Maxx®
2743	Set (grub) screws, 3mm hardened (12)	2000	mount)
3642X 5480X	Shoulder screws, Ultra Shocks (3x12 hex drive) (6) Wheel wrench, splined, 17mm	2085X	Servo, digital high-torque, metal gear (ball bearing), waterproof/ servo saver spring/ steering link
	LED Lights	6553X	Telemetry expander 2.0 and GPS module 2.0, TQi radio system
7882	Extension harness, LED lights (high-voltage)	6550X	Telemetry expander 2.0, TQi radio system (for use only with
6590	High-Voltage Power Amplifier		#6551X GPS module)
7884	LED light bar, front (high-voltage) (40 white LEDs (double row), 82mm wide) (fits X-Maxx® or Maxx®)	6551X	Telemetry GPS module 2.0, TQi radio system (for use only with #6550X telemetry expander)
7883	LED light bar, rear, red (with white reverse light) (high-voltage)	6509R	TQi 2.4 GHz High Output radio system, 2-channel, Traxxas Link™ enabled, TSM (2-ch transmitter, 5-ch micro receiver)
7005	(24 red LEDs, 24 white LEDs, 100mm wide)/ light bar mount (fits X-Maxx® or Maxx®)	6507R	TQi 2.4 GHz High Output radio system, 4-channel with Traxxas Link™ Wireless Module, TSM (4-ch transmitter, 5-ch micro
7885	LED light kit, complete (includes #6590 high-voltage power amplifier)	6528	receiver) Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 2-
	Motors & Electronics		channel (transmitter only)
7749	Adapter, standard servo (adapts standard servo to fit in X-Maxx® or Maxx®)	6529	Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 3- channel (transmitter only)
3475	Cooling fan, Velineon® VXL ESC (fits VXL-6s & VXL-8s)	6530	Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 4-
7787	Covers, gear (3)	6511	channel (transmitter only) Traxxas Link™ Wireless Module
3474	Dual cooling fan kit (with shroud), Velineon® 1200XL motor	0011	
2087 2087X	Gear set (for 2085 servo) Gear set, metal (for 2085 & 2085X servos)	77000	Ready-To-Race Model
3362	Heat sink, Velineon® 1600XL	77086-4	X-Maxx®: Brushless Electric Monster Truck with TQi™ Traxxas Link™ Enabled 2.4GHz Radio System & Traxxas Stability
7760	Motor mounts (front and rear)/ pins (2)		Management (TSM)®
3491 3492	Motor, Velineon® 1200XL, brushless		Rear Suspension
J 4 82	Rebuild kit, Velineon® 1200XL (includes plastic endbells (2), 6x17x6mm ball bearings (2), 6x8x.3 washer (1), 6x8x1 washer (1),	7726	Bulkhead tie bar, upper (1)/ lower (2) (steel)
	7x6x12 spacer (1))	7727X	Bulkhead, rear (upper & lower), center differential (replacing #7727 &
2086	Servo case/gaskets (for 2085 & 2085X servos)		#7728 requires #5107A ball bearings (2))

_	e 3 X-Maxx®: TQi™ Traxxas Link™ Enabled 2.4GHz R	auio & i	SM® (Model 77086-4) Parts List
7752	X Carriers, stub axle (left & right) (requires 20x32x7 ball bearings)	7761R	Shocks, GTX, aluminum (red-anodized) (fully assembled w/o
7716	Mount, tie bar, front (1)/ rear (1)		springs) (2)
7738	Shock tower, rear (left & right halves)	7761T	Shocks, GTX, aluminum, orange-anodized (fully assembled w/o
7831	Suspension arm, black, lower (left, front or rear), heavy duty (1)		springs) (2)
7830		1667	Silicone shock oil (30 wt), 60cc
7829		7767	Spring retainer (adjuster), blue-anodized aluminum, GTX shocks
	duty (2)	77670	(4) (assembled with o-ring)
7831		7767G	Spring retainer (adjuster), green-anodized aluminum, GTX shocks (4) (assembled with o-ring)
7830		7767X	Spring retainer (adjuster), PTFE-coated aluminum, GTX shocks
7831 7830	, , , , , , , , , , , , , , , , , , , ,	11017	(4) (assembled with o-ring)
7030	(1)	7767R	Spring retainer (adjuster), red-anodized aluminum, GTX shocks
7831	• •		(4) (assembled with o-ring)
7830		7853	Springs, shock (natural finish) (GTX) (0.824 rate, white stripe) (2)
	(1)	7854	Springs, shock (natural finish) (GTX) (0.929 rate, orange stripe)
7831	• •		(2)
7830		7766	Springs, shock (natural finish) (GTX) (1.055 rate) (2)
7831	A Suspension arm, white, lower (left, front or rear), heavy duty (1)	7855	Springs, shock (natural finish) (GTX) (1.199 rate, green stripe) (2)
7830	A Suspension arm, white, lower (right, front or rear), heavy duty (1)	7856	Springs, shock (natural finish) (GTX) (1.346 rate, blue stripe) (2)
7829	X Suspension arms, blue, upper (left or right, front or rear), heavy	7857	Springs, shock (natural finish) (GTX) (1.450 rate, black stripe) (2)
	duty (2)	7858	Springs, shock (natural finish) (GTX) (1.538 rate, red stripe) (2)
7829	. , , , , , , , , , , , , , , , , , , ,		Spur Gears & Pinion Gears
	duty (2)	6484X	Gear, 11-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw
7731	, , , , , , , , , , , , , , , , , , , ,		(for use only with steel spur gears)
7730		6485X	Gear, 12-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw
7829	, , , , , , , , , , , , , , , , , , , ,		(for use only with steel spur gears)
=000	heavy duty (2)	6486X	Gear, 13-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw
7829			(for use only with steel spur gears)
7700	duty (2)	6488X	Gear, 14-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw
7729		6487X	Gear, 15-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw
7829	A Suspension arms, white, upper (left or right, front or rear), heavy duty (2)	6489X	Gear, 16-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw
7743		6490X	Gear, 17-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw
7740	' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' '	6491X	Gear, 18-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw
7740	(1), 4x47mm (3), 4x33mm (2) (qty 4, #7740 required for complete set)	6494X	Gear, 20-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw
7742		6495X	Gear, 22-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw
	4x25mm (2), 4x38mm (2)	6496X	Gear, 24-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw
7741		6447R	Spur gear, 46-tooth, steel (wide-face, 1.0 metric pitch)
	Shock Oil	6448R	Spur gear, 50-tooth, steel (wide-face, 1.0 metric pitch)
		6449X	Spur gear, 54-tooth, steel (1.0 metric pitch)
5031		6449R	Spur gear, 54-tooth, steel (wide-face, 1.0 metric pitch)
5032	Oil, shock (30 wt, 350 cSt, 60cc) (silicone)	6449R	Spur gear, 54-tooth, steel (wide-face, 1.0 metric pitch) Steering Commonents
5032 5033	Oil, shock (30 wt, 350 cSt, 60cc) (silicone) Oil, shock (40 wt, 500 cSt, 60cc) (silicone)	6449R 5119	Steering Components
5032 5033 5034	Oil, shock (30 wt, 350 cSt, 60cc) (silicone) Oil, shock (40 wt, 500 cSt, 60cc) (silicone) Oil, shock (50 wt, 600 cSt, 60cc) (silicone)		
5032 5033 5034 5035	Oil, shock (30 wt, 350 cSt, 60cc) (silicone) Oil, shock (40 wt, 500 cSt, 60cc) (silicone) Oil, shock (50 wt, 600 cSt, 60cc) (silicone) Oil, shock (60 wt, 700 cSt, 60cc) (silicone)	5119	Steering Components Ball bearings, blue rubber sealed (10x15x4mm) (2)
5032 5033 5034 5035 5036	Oil, shock (30 wt, 350 cSt, 60cc) (silicone) Oil, shock (40 wt, 500 cSt, 60cc) (silicone) Oil, shock (50 wt, 600 cSt, 60cc) (silicone) Oil, shock (60 wt, 700 cSt, 60cc) (silicone) Oil, shock (70 wt, 900 cSt, 60cc) (silicone)	5119 5116	Sigering Components Ball bearings, blue rubber sealed (10x15x4mm) (2) Ball bearings, blue rubber sealed (5x11x4mm) (2)
5032 5033 5034 5035 5036 5037	Oil, shock (30 wt, 350 cSt, 60cc) (silicone) Oil, shock (40 wt, 500 cSt, 60cc) (silicone) Oil, shock (50 wt, 600 cSt, 60cc) (silicone) Oil, shock (60 wt, 700 cSt, 60cc) (silicone) Oil, shock (70 wt, 900 cSt, 60cc) (silicone) Oil, shock (80 wt, 1,000 cSt, 60cc) (silicone)	5119 5116	SIGATINE COMMINITIES Ball bearings, blue rubber sealed (10x15x4mm) (2) Ball bearings, blue rubber sealed (5x11x4mm) (2) Servo horn, steering/ linkage, steering (46mm, assembled with pivot
5032 5033 5034 5035 5036 5037 5029	Oil, shock (30 wt, 350 cSt, 60cc) (silicone) Oil, shock (40 wt, 500 cSt, 60cc) (silicone) Oil, shock (50 wt, 600 cSt, 60cc) (silicone) Oil, shock (60 wt, 700 cSt, 60cc) (silicone) Oil, shock (70 wt, 900 cSt, 60cc) (silicone) Oil, shock (80 wt, 1,000 cSt, 60cc) (silicone) Shock oil bottle (60cc) (for mixing shock oil)	5119 5116 7747 7746	Steering Components Ball bearings, blue rubber sealed (10x15x4mm) (2) Ball bearings, blue rubber sealed (5x11x4mm) (2) Servo horn, steering/ linkage, steering (46mm, assembled with pivot balls) Steering bellcranks/ bellcrank support/servo saver/ servo saver spring/ draglink/ 3x20mm shoulder screws (2)
5032 5033 5034 5035 5036 5037	Oil, shock (30 wt, 350 cSt, 60cc) (silicone) Oil, shock (40 wt, 500 cSt, 60cc) (silicone) Oil, shock (50 wt, 600 cSt, 60cc) (silicone) Oil, shock (60 wt, 700 cSt, 60cc) (silicone) Oil, shock (70 wt, 900 cSt, 60cc) (silicone) Oil, shock (80 wt, 1,000 cSt, 60cc) (silicone) Shock (80 wt, 1,000 cSt, 60cc) (silicone) Shock oil bottle (60cc) (for mixing shock oil) X Shock oil set (includes 20 wt, 30 wt, 40 wt, 50 wt, 60 wt, 70 wt, &	5119 5116 7747	Ball bearings, blue rubber sealed (10x15x4mm) (2) Ball bearings, blue rubber sealed (5x11x4mm) (2) Servo horn, steering/ linkage, steering (46mm, assembled with pivot balls) Steering bellcranks/ bellcrank support/servo saver/ servo saver spring/ draglink/ 3x20mm shoulder screws (2) Steering link, steel/ servo saver spring, heavy duty (use with
5032 5033 5034 5035 5036 5037 5029 5038	Oil, shock (30 wt, 350 cSt, 60cc) (silicone) Oil, shock (40 wt, 500 cSt, 60cc) (silicone) Oil, shock (50 wt, 600 cSt, 60cc) (silicone) Oil, shock (60 wt, 700 cSt, 60cc) (silicone) Oil, shock (70 wt, 900 cSt, 60cc) (silicone) Oil, shock (80 wt, 1,000 cSt, 60cc) (silicone) Oil, shock (80 wt, 1,000 cSt, 60cc) (silicone) Shock oil bottle (60cc) (for mixing shock oil) X Shock oil set (includes 20 wt, 30 wt, 40 wt, 50 wt, 60 wt, 70 wt, & 80 wt premium shock oils with spinning carousel rack)	5119 5116 7747 7746 7746X	Ball bearings, blue rubber sealed (10x15x4mm) (2) Ball bearings, blue rubber sealed (5x11x4mm) (2) Servo horn, steering/ linkage, steering (46mm, assembled with pivot balls) Steering bellcranks/ bellcrank support/servo saver/ servo saver spring/ draglink/ 3x20mm shoulder screws (2) Steering link, steel/ servo saver spring, heavy duty (use with #2085X metal gear servo)
5032 5033 5034 5035 5036 5037 5029 5038	Oil, shock (30 wt, 350 cSt, 60cc) (silicone) Oil, shock (40 wt, 500 cSt, 60cc) (silicone) Oil, shock (50 wt, 600 cSt, 60cc) (silicone) Oil, shock (60 wt, 700 cSt, 60cc) (silicone) Oil, shock (70 wt, 900 cSt, 60cc) (silicone) Oil, shock (80 wt, 1,000 cSt, 60cc) (silicone) Oil, shock (80 wt, 1,000 cSt, 60cc) (silicone) Shock oil bottle (60cc) (for mixing shock oil) X Shock oil set (includes 20 wt, 30 wt, 40 wt, 50 wt, 60 wt, 70 wt, & 80 wt premium shock oils with spinning carousel rack) Silicone shock oil (30 wt), 60cc	5119 5116 7747 7746	Stepring Commonates Ball bearings, blue rubber sealed (10x15x4mm) (2) Ball bearings, blue rubber sealed (5x11x4mm) (2) Servo horn, steering/ linkage, steering (46mm, assembled with pivot balls) Steering bellcranks/ bellcrank support/servo saver/ servo saver spring/ draglink/ 3x20mm shoulder screws (2) Steering link, steel/ servo saver spring, heavy duty (use with #2085X metal gear servo) Toe links, molded composite, 173mm (158mm center to center)
5032 5033 5034 5035 5036 5037 5029 5038	Oil, shock (30 wt, 350 cSt, 60cc) (silicone) Oil, shock (40 wt, 500 cSt, 60cc) (silicone) Oil, shock (50 wt, 600 cSt, 60cc) (silicone) Oil, shock (60 wt, 700 cSt, 60cc) (silicone) Oil, shock (70 wt, 900 cSt, 60cc) (silicone) Oil, shock (80 wt, 1,000 cSt, 60cc) (silicone) Shock (80 wt, 1,000 cSt, 60cc) (silicone) Shock oil bottle (60cc) (for mixing shock oil) X Shock oil set (includes 20 wt, 30 wt, 40 wt, 50 wt, 60 wt, 70 wt, & 80 wt premium shock oils with spinning carousel rack) Silicone shock oil (30 wt), 60cc Spinning carousel rack	5119 5116 7747 7746 7746X 7748	Ball bearings, blue rubber sealed (10x15x4mm) (2) Ball bearings, blue rubber sealed (5x11x4mm) (2) Servo horn, steering/ linkage, steering (46mm, assembled with pivot balls) Steering bellcranks/ bellcrank support/servo saver/ servo saver spring/ draglink/ 3x20mm shoulder screws (2) Steering link, steel/ servo saver spring, heavy duty (use with #2085X metal gear servo) Toe links, molded composite, 173mm (158mm center to center) (black) (2)
5032 5033 5034 5035 5036 5037 5029 5038	Oil, shock (30 wt, 350 cSt, 60cc) (silicone) Oil, shock (40 wt, 500 cSt, 60cc) (silicone) Oil, shock (50 wt, 600 cSt, 60cc) (silicone) Oil, shock (60 wt, 700 cSt, 60cc) (silicone) Oil, shock (70 wt, 900 cSt, 60cc) (silicone) Oil, shock (80 wt, 1,000 cSt, 60cc) (silicone) Shock (80 wt, 1,000 cSt, 60cc) (silicone) Shock oil bottle (60cc) (for mixing shock oil) X Shock oil set (includes 20 wt, 30 wt, 40 wt, 50 wt, 60 wt, 70 wt, & 80 wt premium shock oils with spinning carousel rack) Silicone shock oil (30 wt), 60cc Spinning carousel rack	5119 5116 7747 7746 7746X	Ball bearings, blue rubber sealed (10x15x4mm) (2) Ball bearings, blue rubber sealed (5x11x4mm) (2) Servo horn, steering/ linkage, steering (46mm, assembled with pivot balls) Steering bellcranks/ bellcrank support/servo saver/ servo saver spring/ draglink/ 3x20mm shoulder screws (2) Steering link, steel/ servo saver spring, heavy duty (use with #2085X metal gear servo) Toe links, molded composite, 173mm (158mm center to center) (black) (2) Toe links, X-Maxx® (TUBES blue-anodized, 7075-T6 aluminum,
5032 5033 5034 5035 5036 5037 5029 5038 1667 5038	Oil, shock (30 wt, 350 cSt, 60cc) (silicone) Oil, shock (40 wt, 500 cSt, 60cc) (silicone) Oil, shock (50 wt, 600 cSt, 60cc) (silicone) Oil, shock (60 wt, 700 cSt, 60cc) (silicone) Oil, shock (70 wt, 900 cSt, 60cc) (silicone) Oil, shock (80 wt, 1,000 cSt, 60cc) (silicone) Shock oil bottle (60cc) (for mixing shock oil) X Shock oil set (includes 20 wt, 30 wt, 40 wt, 50 wt, 60 wt, 70 wt, & 80 wt premium shock oils with spinning carousel rack) Silicone shock oil (30 wt), 60cc Spinning carousel rack SIDCKS (FTN) A Body, GTX shock (aluminum, black-anodized) (1)	5119 5116 7747 7746 7746X 7748	Ball bearings, blue rubber sealed (10x15x4mm) (2) Ball bearings, blue rubber sealed (5x11x4mm) (2) Servo horn, steering/ linkage, steering (46mm, assembled with pivot balls) Steering bellcranks/ bellcrank support/servo saver/ servo saver spring/ draglink/ 3x20mm shoulder screws (2) Steering link, steel/ servo saver spring, heavy duty (use with #2085X metal gear servo) Toe links, molded composite, 173mm (158mm center to center) (black) (2) Toe links, X-Maxx® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with
5032 5033 5034 5035 5036 5037 5029 5038 1667 5038	Oil, shock (30 wt, 350 cSt, 60cc) (silicone) Oil, shock (40 wt, 500 cSt, 60cc) (silicone) Oil, shock (50 wt, 600 cSt, 60cc) (silicone) Oil, shock (60 wt, 700 cSt, 60cc) (silicone) Oil, shock (70 wt, 900 cSt, 60cc) (silicone) Oil, shock (80 wt, 1,000 cSt, 60cc) (silicone) Oil, shock (80 wt, 1,000 cSt, 60cc) (silicone) Shock oil bottle (60cc) (for mixing shock oil) X Shock oil set (includes 20 wt, 30 wt, 40 wt, 50 wt, 60 wt, 70 wt, & 80 wt premium shock oils with spinning carousel rack) Silicone shock oil (30 wt), 60cc Spinning carousel rack SIDELS [FILI] A Body, GTX shock (aluminum, black-anodized) (1) Body, GTX shock (aluminum, blue-anodized) (1)	5119 5116 7747 7746 7746X 7748 7748X	Ball bearings, blue rubber sealed (10x15x4mm) (2) Ball bearings, blue rubber sealed (5x11x4mm) (2) Servo horn, steering/ linkage, steering (46mm, assembled with pivot balls) Steering bellcranks/ bellcrank support/servo saver/ servo saver spring/ draglink/ 3x20mm shoulder screws (2) Steering link, steel/ servo saver spring, heavy duty (use with #2085X metal gear servo) Toe links, molded composite, 173mm (158mm center to center) (black) (2) Toe links, X-Maxx® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1)
5032 5033 5034 5035 5036 5037 5029 5038 1667 5038 7765 7765	Oil, shock (30 wt, 350 cSt, 60cc) (silicone) Oil, shock (40 wt, 500 cSt, 60cc) (silicone) Oil, shock (50 wt, 600 cSt, 60cc) (silicone) Oil, shock (60 wt, 700 cSt, 60cc) (silicone) Oil, shock (70 wt, 900 cSt, 60cc) (silicone) Oil, shock (80 wt, 1,000 cSt, 60cc) (silicone) Oil, shock (80 wt, 1,000 cSt, 60cc) (silicone) Shock oil bottle (60cc) (for mixing shock oil) X Shock oil set (includes 20 wt, 30 wt, 40 wt, 50 wt, 60 wt, 70 wt, & 80 wt premium shock oils with spinning carousel rack) Silicone shock oil (30 wt), 60cc Spinning carousel rack SIDE S [FIN] A Body, GTX shock (aluminum, black-anodized) (1) Body, GTX shock (aluminum, green-anodized) (1)	5119 5116 7747 7746 7746X 7748	Ball bearings, blue rubber sealed (10x15x4mm) (2) Ball bearings, blue rubber sealed (5x11x4mm) (2) Servo horn, steering/ linkage, steering (46mm, assembled with pivot balls) Steering bellcranks/ bellcrank support/servo saver/ servo saver spring/ draglink/ 3x20mm shoulder screws (2) Steering link, steel/ servo saver spring, heavy duty (use with #2085X metal gear servo) Toe links, molded composite, 173mm (158mm center to center) (black) (2) Toe links, X-Maxx® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with
5032 5033 5034 5035 5036 5037 5029 5038 1667 5038 7765 7765	Oil, shock (30 wt, 350 cSt, 60cc) (silicone) Oil, shock (40 wt, 500 cSt, 60cc) (silicone) Oil, shock (50 wt, 600 cSt, 60cc) (silicone) Oil, shock (60 wt, 700 cSt, 60cc) (silicone) Oil, shock (70 wt, 900 cSt, 60cc) (silicone) Oil, shock (80 wt, 1,000 cSt, 60cc) (silicone) Shock oil bottle (60cc) (for mixing shock oil) X Shock oil set (includes 20 wt, 30 wt, 40 wt, 50 wt, 60 wt, 70 wt, & 80 wt premium shock oils with spinning carousel rack) Silicone shock oil (30 wt), 60cc Spinning carousel rack SIDCLS [CIT] A Body, GTX shock (aluminum, blue-anodized) (1) Body, GTX shock (aluminum, green-anodized) (1) Body, GTX shock (aluminum, orange-anodized) (1)	5119 5116 7747 7746 7746X 7748 7748X	Ball bearings, blue rubber sealed (10x15x4mm) (2) Ball bearings, blue rubber sealed (5x11x4mm) (2) Servo horn, steering/ linkage, steering (46mm, assembled with pivot balls) Steering bellcranks/ bellcrank support/servo saver/ servo saver spring/ draglink/ 3x20mm shoulder screws (2) Steering link, steel/ servo saver spring, heavy duty (use with #2085X metal gear servo) Toe links, molded composite, 173mm (158mm center to center) (black) (2) Toe links, X-Maxx® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES green-anodized, 7075-T6 aluminum,
5032 5033 5034 5035 5036 5037 5029 5038 1667 5038 7765 7765 7765	Oil, shock (30 wt, 350 cSt, 60cc) (silicone) Oil, shock (40 wt, 500 cSt, 60cc) (silicone) Oil, shock (50 wt, 600 cSt, 60cc) (silicone) Oil, shock (60 wt, 700 cSt, 60cc) (silicone) Oil, shock (70 wt, 900 cSt, 60cc) (silicone) Oil, shock (80 wt, 1,000 cSt, 60cc) (silicone) Shock oil bottle (60cc) (for mixing shock oil) X Shock oil set (includes 20 wt, 30 wt, 40 wt, 50 wt, 60 wt, 70 wt, & 80 wt premium shock oils with spinning carousel rack) Silicone shock oil (30 wt), 60cc Spinning carousel rack SIDELS [FIN] A Body, GTX shock (aluminum, black-anodized) (1) Body, GTX shock (aluminum, green-anodized) (1) Body, GTX shock (aluminum, orange-anodized) (1) Body, GTX shock (aluminum, red-anodized) (1) Body, GTX shock (aluminum, red-anodized) (1)	5119 5116 7747 7746 7746X 7748 7748X	Ball bearings, blue rubber sealed (10x15x4mm) (2) Ball bearings, blue rubber sealed (5x11x4mm) (2) Servo horn, steering/ linkage, steering (46mm, assembled with pivot balls) Steering bellcranks/ bellcrank support/servo saver/ servo saver spring/ draglink/ 3x20mm shoulder screws (2) Steering link, steel/ servo saver spring, heavy duty (use with #2085X metal gear servo) Toe links, molded composite, 173mm (158mm center to center) (black) (2) Toe links, X-Maxx® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with
5032 5033 5034 5035 5036 5037 5029 5038 1667 5038 7765 7765 7765 7765	Oil, shock (30 wt, 350 cSt, 60cc) (silicone) Oil, shock (40 wt, 500 cSt, 60cc) (silicone) Oil, shock (50 wt, 600 cSt, 60cc) (silicone) Oil, shock (60 wt, 700 cSt, 60cc) (silicone) Oil, shock (70 wt, 900 cSt, 60cc) (silicone) Oil, shock (80 wt, 1,000 cSt, 60cc) (silicone) Shock oil bottle (60cc) (for mixing shock oil) X Shock oil set (includes 20 wt, 30 wt, 40 wt, 50 wt, 60 wt, 70 wt, & 80 wt premium shock oils with spinning carousel rack) Silicone shock oil (30 wt), 60cc Spinning carousel rack SIDELS (FIN) A Body, GTX shock (aluminum, blue-anodized) (1) Body, GTX shock (aluminum, green-anodized) (1) T Body, GTX shock (aluminum, orange-anodized) (1) Body, GTX shock (aluminum, red-anodized) (1)	5119 5116 7747 7746 7746X 7748 X 7748X	Ball bearings, blue rubber sealed (10x15x4mm) (2) Ball bearings, blue rubber sealed (5x11x4mm) (2) Servo horn, steering/ linkage, steering (46mm, assembled with pivot balls) Steering bellcranks/ bellcrank support/servo saver/ servo saver spring/ draglink/ 3x20mm shoulder screws (2) Steering link, steel/ servo saver spring, heavy duty (use with #2085X metal gear servo) Toe links, molded composite, 173mm (158mm center to center) (black) (2) Toe links, X-Maxx® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with
5032 5033 5034 5035 5036 5037 5029 5038 1667 5038 7765 7765 7765	Oil, shock (30 wt, 350 cSt, 60cc) (silicone) Oil, shock (40 wt, 500 cSt, 60cc) (silicone) Oil, shock (50 wt, 600 cSt, 60cc) (silicone) Oil, shock (60 wt, 700 cSt, 60cc) (silicone) Oil, shock (70 wt, 900 cSt, 60cc) (silicone) Oil, shock (80 wt, 1,000 cSt, 60cc) (silicone) Oil, shock (80 wt, 1,000 cSt, 60cc) (silicone) Shock oil bottle (60cc) (for mixing shock oil) X Shock oil set (includes 20 wt, 30 wt, 40 wt, 50 wt, 60 wt, 70 wt, & 80 wt premium shock oils with spinning carousel rack) Silicone shock oil (30 wt), 60cc Spinning carousel rack SIDEKS (GTN) A Body, GTX shock (aluminum, black-anodized) (1) Body, GTX shock (aluminum, green-anodized) (1) Body, GTX shock (aluminum, orange-anodized) (1) Body, GTX shock (aluminum, red-anodized) (1) Rebuild kit, GTX shocks (lower cartridge, assembled, pistons, piston	5119 5116 7747 7746 7746X 7748 X 7748X	Ball bearings, blue rubber sealed (10x15x4mm) (2) Ball bearings, blue rubber sealed (5x11x4mm) (2) Servo horn, steering/ linkage, steering (46mm, assembled with pivot balls) Steering bellcranks/ bellcrank support/servo saver/ servo saver spring/ draglink/ 3x20mm shoulder screws (2) Steering link, steel/ servo saver spring, heavy duty (use with #2085X metal gear servo) Toe links, molded composite, 173mm (158mm center to center) (black) (2) Toe links, X-Maxx® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum,
5032 5033 5034 5035 5036 5037 5029 5038 7765 7765 7765 7765 7765	Oil, shock (30 wt, 350 cSt, 60cc) (silicone) Oil, shock (40 wt, 500 cSt, 60cc) (silicone) Oil, shock (50 wt, 600 cSt, 60cc) (silicone) Oil, shock (60 wt, 700 cSt, 60cc) (silicone) Oil, shock (70 wt, 900 cSt, 60cc) (silicone) Oil, shock (80 wt, 1,000 cSt, 60cc) (silicone) Oil, shock (80 wt, 1,000 cSt, 60cc) (silicone) Shock oil bottle (60cc) (for mixing shock oil) X Shock oil set (includes 20 wt, 30 wt, 40 wt, 50 wt, 60 wt, 70 wt, & 80 wt premium shock oils with spinning carousel rack) Silicone shock oil (30 wt), 60cc Spinning carousel rack SIDCKS (GTX) A Body, GTX shock (aluminum, black-anodized) (1) Body, GTX shock (aluminum, green-anodized) (1) Body, GTX shock (aluminum, orange-anodized) (1) Rody, GTX shock (aluminum, red-anodized) (1) Rody, GTX shock (aluminum, red-anodized) (1) Rody, GTX shock (fard-anodized, PTFE-coated aluminum) (1) Rebuild kit, GTX shocks (lower cartridge, assembled, pistons, piston nuts, bladders) (renews 2 shocks)	5119 5116 7747 7746 7746X 7748 X 7748X	Ball bearings, blue rubber sealed (10x15x4mm) (2) Ball bearings, blue rubber sealed (5x11x4mm) (2) Servo horn, steering/ linkage, steering (46mm, assembled with pivot balls) Steering bellcranks/ bellcrank support/servo saver/ servo saver spring/ draglink/ 3x20mm shoulder screws (2) Steering link, steel/ servo saver spring, heavy duty (use with #2085X metal gear servo) Toe links, molded composite, 173mm (158mm center to center) (black) (2) Toe links, X-Maxx® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1)
5032 5033 5034 5035 5036 5037 5029 5038 1667 5038 7765 7765 7765 7765	Oil, shock (30 wt, 350 cSt, 60cc) (silicone) Oil, shock (40 wt, 500 cSt, 60cc) (silicone) Oil, shock (50 wt, 600 cSt, 60cc) (silicone) Oil, shock (60 wt, 700 cSt, 60cc) (silicone) Oil, shock (70 wt, 900 cSt, 60cc) (silicone) Oil, shock (80 wt, 1,000 cSt, 60cc) (silicone) Oil, shock (80 wt, 1,000 cSt, 60cc) (silicone) Shock oil bottle (60cc) (for mixing shock oil) X Shock oil set (includes 20 wt, 30 wt, 40 wt, 50 wt, 60 wt, 70 wt, & 80 wt premium shock oils with spinning carousel rack) Silicone shock oil (30 wt), 60cc Spinning carousel rack SIDELS [FILI] A Body, GTX shock (aluminum, black-anodized) (1) Body, GTX shock (aluminum, green-anodized) (1) Body, GTX shock (aluminum, orange-anodized) (1) Body, GTX shock (aluminum, red-anodized) (1) Rody, GTX shock (aluminum, red-anodized) (1) Rody, GTX shock (lauminum, red-anodized) (1)	5119 5116 7747 7746 7746X 7748 7748X 7748G 7748R	Ball bearings, blue rubber sealed (10x15x4mm) (2) Ball bearings, blue rubber sealed (5x11x4mm) (2) Servo horn, steering/ linkage, steering (46mm, assembled with pivot balls) Steering bellcranks/ bellcrank support/servo saver/ servo saver spring/ draglink/ 3x20mm shoulder screws (2) Steering bellcranks/ bellcrank support/servo saver/ servo saver spring/ draglink/ 3x20mm shoulder screws (2) Steering link, steel/ servo saver spring, heavy duty (use with #2085X metal gear servo) Toe links, molded composite, 173mm (158mm center to center) (black) (2) Toe links, X-Maxx® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1)
5032 5033 5034 5035 5036 5037 5029 5038 1667 5038 7765 7765 7765 7765 7765 7762	Oil, shock (30 wt, 350 cSt, 60cc) (silicone) Oil, shock (40 wt, 500 cSt, 60cc) (silicone) Oil, shock (50 wt, 600 cSt, 60cc) (silicone) Oil, shock (60 wt, 700 cSt, 60cc) (silicone) Oil, shock (70 wt, 900 cSt, 60cc) (silicone) Oil, shock (80 wt, 1,000 cSt, 60cc) (silicone) Oil, shock (80 wt, 1,000 cSt, 60cc) (silicone) Shock oil bottle (60cc) (for mixing shock oil) X Shock oil set (includes 20 wt, 30 wt, 40 wt, 50 wt, 60 wt, 70 wt, & 80 wt premium shock oils with spinning carousel rack) Silicone shock oil (30 wt), 60cc Spinning carousel rack SIDELS [FIII] A Body, GTX shock (aluminum, blue-anodized) (1) Body, GTX shock (aluminum, green-anodized) (1) Body, GTX shock (aluminum, orange-anodized) (1) R Body, GTX shock (aluminum, red-anodized) (1) R Body, GTX shock (aluminum, red-anodized) (1) R Body, GTX shock (fard-anodized, PTFE-coated aluminum) (1) Rebuild kit, GTX shocks (lower cartridge, assembled, pistons, piston nuts, bladders) (renews 2 shocks) Shaft, GTX shock, 110mm (assembled with rod ends & hollow balls) (steel, chrome finish) (2)	5119 5116 7747 7746 7746X 7748 X 7748X	Ball bearings, blue rubber sealed (10x15x4mm) (2) Ball bearings, blue rubber sealed (5x11x4mm) (2) Servo horn, steering/ linkage, steering (46mm, assembled with pivot balls) Steering bellcranks/ bellcrank support/servo saver/ servo saver spring/ draglink/ 3x20mm shoulder screws (2) Steering link, steel/ servo saver spring, heavy duty (use with #2085X metal gear servo) Toe links, molded composite, 173mm (158mm center to center) (black) (2) Toe links, X-Maxx® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) SUSTIBLISTON LITHINGS.
5032 5033 5034 5035 5036 5037 5029 5038 7765 7765 7765 7765 7765	Oil, shock (30 wt, 350 cSt, 60cc) (silicone) Oil, shock (40 wt, 500 cSt, 60cc) (silicone) Oil, shock (50 wt, 600 cSt, 60cc) (silicone) Oil, shock (60 wt, 700 cSt, 60cc) (silicone) Oil, shock (70 wt, 900 cSt, 60cc) (silicone) Oil, shock (80 wt, 1,000 cSt, 60cc) (silicone) Oil, shock (80 wt, 1,000 cSt, 60cc) (silicone) Shock oil bottle (60cc) (for mixing shock oil) X Shock oil set (includes 20 wt, 30 wt, 40 wt, 50 wt, 60 wt, 70 wt, & 80 wt premium shock oils with spinning carousel rack) Silicone shock oil (30 wt), 60cc Spinning carousel rack SIDELS (FIN) A Body, GTX shock (aluminum, black-anodized) (1) Body, GTX shock (aluminum, green-anodized) (1) Body, GTX shock (aluminum, orange-anodized) (1) R Body, GTX shock (aluminum, red-anodized) (1) R Body, GTX shock (fauminum, red-anodized) (1) R Body, GTX shock (fauminum, red-anodized) (1) Rebuild kit, GTX shocks (lower cartridge, assembled, pistons, piston nuts, bladders) (renews 2 shocks) Shaft, GTX shock, 110mm (assembled with rod ends & hollow balls) (steel, chrome finish) (2) Shaft, GTX shock, TiN-coated (2) (assembled with rod ends and	5119 5116 7747 7746 7746X 7748 7748X 7748G 7748R	Ball bearings, blue rubber sealed (10x15x4mm) (2) Ball bearings, blue rubber sealed (5x11x4mm) (2) Servo horn, steering/ linkage, steering (46mm, assembled with pivot balls) Steering bellcranks/ bellcrank support/servo saver/ servo saver spring/ draglink/ 3x20mm shoulder screws (2) Steering link, steel/ servo saver spring, heavy duty (use with #2085X metal gear servo) Toe links, molded composite, 173mm (158mm center to center) (black) (2) Toe links, X-Maxx® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) SUSTICING OF TABLES (TOBLES) (1) FOR TABLES
5032 5033 5034 5035 5036 5037 5029 5038 7765 7765 7765 7765 7765 7763	Oil, shock (30 wt, 350 cSt, 60cc) (silicone) Oil, shock (40 wt, 500 cSt, 60cc) (silicone) Oil, shock (50 wt, 600 cSt, 60cc) (silicone) Oil, shock (60 wt, 700 cSt, 60cc) (silicone) Oil, shock (70 wt, 900 cSt, 60cc) (silicone) Oil, shock (80 wt, 1,000 cSt, 60cc) (silicone) Oil, shock (80 wt, 1,000 cSt, 60cc) (silicone) Shock oil bottle (60cc) (for mixing shock oil) X Shock oil set (includes 20 wt, 30 wt, 40 wt, 50 wt, 60 wt, 70 wt, & 80 wt premium shock oils with spinning carousel rack) Silicone shock oil (30 wt), 60cc Spinning carousel rack SIDELS (STN) A Body, GTX shock (aluminum, black-anodized) (1) Body, GTX shock (aluminum, preen-anodized) (1) Body, GTX shock (aluminum, orange-anodized) (1) R Body, GTX shock (aluminum, red-anodized) (1) R Body, GTX shock (fauminum, red-anodized) (1) Rebuild kit, GTX shock (lower cartridge, assembled, pistons, piston nuts, bladders) (renews 2 shocks) Shaft, GTX shock, 110mm (assembled with rod ends & hollow balls) (steel, chrome finish) (2) Shaft, GTX shock, TiN-coated (2) (assembled with rod ends and steel hollow balls)	5119 5116 7747 7746 7746X 7748 X 7748 X 7748 G 7748 R	Ball bearings, blue rubber sealed (10x15x4mm) (2) Ball bearings, blue rubber sealed (5x11x4mm) (2) Servo horn, steering/ linkage, steering (46mm, assembled with pivot balls) Steering bellcranks/ bellcrank support/servo saver/ servo saver spring/ draglink/ 3x20mm shoulder screws (2) Steering link, steel/ servo saver spring, heavy duty (use with #2085X metal gear servo) Toe links, molded composite, 173mm (158mm center to center) (black) (2) Toe links, X-Maxx® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) SISSIBIS OF Links (1) Insert, threaded steel (replacement inserts for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) (includes (1) left and (1) right threaded insert)
5032 5033 5034 5035 5036 5037 5029 5038 1667 5038 7765 7765 7765 7765 7765 7762	Oil, shock (30 wt, 350 cSt, 60cc) (silicone) Oil, shock (40 wt, 500 cSt, 60cc) (silicone) Oil, shock (50 wt, 600 cSt, 60cc) (silicone) Oil, shock (60 wt, 700 cSt, 60cc) (silicone) Oil, shock (70 wt, 900 cSt, 60cc) (silicone) Oil, shock (80 wt, 1,000 cSt, 60cc) (silicone) Oil, shock (80 wt, 1,000 cSt, 60cc) (silicone) Shock oil bottle (60cc) (for mixing shock oil) X Shock oil set (includes 20 wt, 30 wt, 40 wt, 50 wt, 60 wt, 70 wt, & 80 wt premium shock oils with spinning carousel rack) Silicone shock oil (30 wt), 60cc Spinning carousel rack SIDEKS (STN) A Body, GTX shock (aluminum, black-anodized) (1) Body, GTX shock (aluminum, green-anodized) (1) Body, GTX shock (aluminum, orange-anodized) (1) Body, GTX shock (aluminum, red-anodized) (1) Rebuild kit, GTX shock (lower cartridge, assembled, pistons, piston nuts, bladders) (renews 2 shocks) Shaft, GTX shock, 110mm (assembled with rod ends & hollow balls) (steel, chrome finish) (2) T Shaft, GTX shock, TiN-coated (2) (assembled with rod ends and steel hollow balls) Shock caps, aluminum (blue-anodized), GTX shocks (4)/ spacers	5119 5116 7747 7746 7746X 7748 7748X 7748G 7748R	Ball bearings, blue rubber sealed (10x15x4mm) (2) Ball bearings, blue rubber sealed (5x11x4mm) (2) Servo horn, steering/ linkage, steering (46mm, assembled with pivot balls) Steering bellcranks/ bellcrank support/servo saver/ servo saver spring/ draglink/ 3x20mm shoulder screws (2) Steering link, steel/ servo saver spring, heavy duty (use with #2085X metal gear servo) Toe links, molded composite, 173mm (158mm center to center) (black) (2) Toe links, X-Maxx® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Insert, threaded steel (replacement inserts for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) (includes (1) left and (1) right threaded insert) Rod ends (4) (assembled with steel pivot balls) (replacement
5032 5033 5034 5035 5036 5037 5029 5038 7765 7765 7765 7765 7762 7763 7763	Oil, shock (30 wt, 350 cSt, 60cc) (silicone) Oil, shock (40 wt, 500 cSt, 60cc) (silicone) Oil, shock (50 wt, 600 cSt, 60cc) (silicone) Oil, shock (60 wt, 700 cSt, 60cc) (silicone) Oil, shock (70 wt, 900 cSt, 60cc) (silicone) Oil, shock (80 wt, 1,000 cSt, 60cc) (silicone) Oil, shock (80 wt, 1,000 cSt, 60cc) (silicone) Shock oil bottle (60cc) (for mixing shock oil) X Shock oil set (includes 20 wt, 30 wt, 40 wt, 50 wt, 60 wt, 70 wt, & 80 wt premium shock oils with spinning carousel rack) Silicone shock oil (30 wt), 60cc Spinning carousel rack SIDCKS (FTK) A Body, GTX shock (aluminum, black-anodized) (1) Body, GTX shock (aluminum, green-anodized) (1) Body, GTX shock (aluminum, orange-anodized) (1) Rody, GTX shock (aluminum, red-anodized) (1) Rody, GTX shock (lauminum, red-anodized) (1) Rody, GTX shock (hard-anodized, PTFE-coated aluminum) (1) Rebuild kit, GTX shocks (lower cartridge, assembled, pistons, piston nuts, bladders) (renews 2 shocks) Shaft, GTX shock, 110mm (assembled with rod ends & hollow balls) (steel, chrome finish) (2) Shaft, GTX shock, TiN-coated (2) (assembled with rod ends and steel hollow balls) A Shock caps, aluminum (blue-anodized), GTX shocks (4)/ spacers (8)	5119 5116 7747 7746 7746X 7748X 7748X 7748G 7748R	Ball bearings, blue rubber sealed (10x15x4mm) (2) Ball bearings, blue rubber sealed (5x11x4mm) (2) Servo horn, steering/ linkage, steering (46mm, assembled with pivot balls) Steering bellcranks/ bellcrank support/servo saver/ servo saver spring/ draglink/ 3x20mm shoulder screws (2) Steering link, steel/ servo saver spring, heavy duty (use with #2085X metal gear servo) Toe links, molded composite, 173mm (158mm center to center) (black) (2) Toe links, X-Maxx® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) SUSTEELS OF LITERS OF #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) (includes (1) left and (1) right threaded insert) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X)
5032 5033 5034 5035 5036 5037 5029 5038 7765 7765 7765 7765 7765 7763	Oil, shock (30 wt, 350 cSt, 60cc) (silicone) Oil, shock (40 wt, 500 cSt, 60cc) (silicone) Oil, shock (50 wt, 600 cSt, 60cc) (silicone) Oil, shock (60 wt, 700 cSt, 60cc) (silicone) Oil, shock (70 wt, 900 cSt, 60cc) (silicone) Oil, shock (80 wt, 1,000 cSt, 60cc) (silicone) Oil, shock (80 wt, 1,000 cSt, 60cc) (silicone) Shock oil bottle (60cc) (for mixing shock oil) X Shock oil set (includes 20 wt, 30 wt, 40 wt, 50 wt, 60 wt, 70 wt, & 80 wt premium shock oils with spinning carousel rack) Silicone shock oil (30 wt), 60cc Spinning carousel rack SIDELS [FIII] A Body, GTX shock (aluminum, black-anodized) (1) Body, GTX shock (aluminum, green-anodized) (1) Body, GTX shock (aluminum, orange-anodized) (1) R Body, GTX shock (aluminum, red-anodized) (1) R Body, GTX shock (aluminum, red-anodized) (1) R Body, GTX shock (hard-anodized, PTFE-coated aluminum) (1) R Body GTX shock (lower cartridge, assembled, pistons, piston nuts, bladders) (renews 2 shocks) Shaft, GTX shock, 110mm (assembled with rod ends & hollow balls) (steel, chrome finish) (2) T Shaft, GTX shock, TiN-coated (2) (assembled with rod ends and steel hollow balls) A Shock caps, aluminum (blue-anodized), GTX shocks (4)/ spacers (8) Shock caps, aluminum (green-anodized), GTX shocks (4)/	5119 5116 7747 7746 7746X 7748X 7748G 7748R 7748R 7798 7797	Ball bearings, blue rubber sealed (10x15x4mm) (2) Ball bearings, blue rubber sealed (5x11x4mm) (2) Servo horn, steering/ linkage, steering (46mm, assembled with pivot balls) Steering bellcranks/ bellcrank support/servo saver/ servo saver spring/ draglink/ 3x20mm shoulder screws (2) Steering link, steel/ servo saver spring, heavy duty (use with #2085X metal gear servo) Toe links, molded composite, 173mm (158mm center to center) (black) (2) Toe links, X-Maxx® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) SISTERS OF Linkage Insert, threaded steel (replacement inserts for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) (includes (1) left and (1) right threaded insert) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #7748G, 7748R, 7748X, 8542A, 8542R, 8748X, 7748X, 8542A, 8542R, 8542T, 8542X) Suspension pin retainer (4)
5032 5033 5034 5035 5036 5037 5029 5038 7765 7765 7765 7765 7765 7763 7763 7764	Oil, shock (30 wt, 350 cSt, 60cc) (silicone) Oil, shock (40 wt, 500 cSt, 60cc) (silicone) Oil, shock (50 wt, 600 cSt, 60cc) (silicone) Oil, shock (60 wt, 700 cSt, 60cc) (silicone) Oil, shock (70 wt, 900 cSt, 60cc) (silicone) Oil, shock (80 wt, 1,000 cSt, 60cc) (silicone) Oil, shock (80 wt, 1,000 cSt, 60cc) (silicone) Shock oil bottle (60cc) (for mixing shock oil) X Shock oil set (includes 20 wt, 30 wt, 40 wt, 50 wt, 60 wt, 70 wt, & 80 wt premium shock oils with spinning carousel rack) Silicone shock oil (30 wt), 60cc Spinning carousel rack SIDE (FIN) A Body, GTX shock (aluminum, black-anodized) (1) Body, GTX shock (aluminum, green-anodized) (1) Body, GTX shock (aluminum, orange-anodized) (1) Body, GTX shock (aluminum, red-anodized) (1) R Body, GTX shock (aluminum, red-anodized) (1) R Body, GTX shock (fard-anodized, PTFE-coated aluminum) (1) Rebuild kit, GTX shocks (lower cartridge, assembled, pistons, piston nuts, bladders) (renews 2 shocks) Shaft, GTX shock, 110mm (assembled with rod ends & hollow balls) (steel, chrome finish) (2) T Shaft, GTX shock, TiN-coated (2) (assembled with rod ends and steel hollow balls) Shock caps, aluminum (blue-anodized), GTX shocks (4)/ spacers (8)	5119 5116 7747 7746 7746X 7748X 7748X 7748G 7748R	Ball bearings, blue rubber sealed (10x15x4mm) (2) Ball bearings, blue rubber sealed (5x11x4mm) (2) Servo horn, steering/ linkage, steering (46mm, assembled with pivot balls) Steering bellcranks/ bellcrank support/servo saver/ servo saver spring/ draglink/ 3x20mm shoulder screws (2) Steering link, steel/ servo saver spring, heavy duty (use with #2085X metal gear servo) Toe links, molded composite, 173mm (158mm center to center) (black) (2) Toe links, X-Maxx® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) SUSTANS OF LITER OF #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) (includes (1) left and (1) right threaded insert) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #7748G, 7748R, 7748R, 8542A, 8542R, 8542T, 8542X) Suspension pin retainer (4) Suspension pin set, front or rear corner (hardened steel), 4x85mm
5032 5033 5034 5035 5036 5037 5029 5038 7765 7765 7765 7765 7762 7763 7763	Oil, shock (30 wt, 350 cSt, 60cc) (silicone) Oil, shock (40 wt, 500 cSt, 60cc) (silicone) Oil, shock (50 wt, 600 cSt, 60cc) (silicone) Oil, shock (60 wt, 700 cSt, 60cc) (silicone) Oil, shock (70 wt, 900 cSt, 60cc) (silicone) Oil, shock (80 wt, 1,000 cSt, 60cc) (silicone) Oil, shock (80 wt, 1,000 cSt, 60cc) (silicone) Shock oil bottle (60cc) (for mixing shock oil) X Shock oil set (includes 20 wt, 30 wt, 40 wt, 50 wt, 60 wt, 70 wt, & 80 wt premium shock oils with spinning carousel rack) Silicone shock oil (30 wt), 60cc Spinning carousel rack SIDE (FIN) A Body, GTX shock (aluminum, black-anodized) (1) Body, GTX shock (aluminum, green-anodized) (1) Body, GTX shock (aluminum, orange-anodized) (1) Body, GTX shock (aluminum, red-anodized) (1) R Body, GTX shock (aluminum, red-anodized) (1) R Body, GTX shock (fard-anodized, PTFE-coated aluminum) (1) Rebuild kit, GTX shocks (lower cartridge, assembled, pistons, piston nuts, bladders) (renews 2 shocks) Shaft, GTX shock, 110mm (assembled with rod ends & hollow balls) (steel, chrome finish) (2) T Shaft, GTX shock, TiN-coated (2) (assembled with rod ends and steel hollow balls) Shock caps, aluminum (blue-anodized), GTX shocks (4)/ spacers (8)	5119 5116 7747 7746 7746X 7748X 7748G 7748R 7798 7798 7797	Ball bearings, blue rubber sealed (10x15x4mm) (2) Ball bearings, blue rubber sealed (5x11x4mm) (2) Servo horn, steering/ linkage, steering (46mm, assembled with pivot balls) Steering bellcranks/ bellcrank support/servo saver/ servo saver spring/ draglink/ 3x20mm shoulder screws (2) Steering link, steel/ servo saver spring, heavy duty (use with #2085X metal gear servo) Toe links, molded composite, 173mm (158mm center to center) (black) (2) Toe links, X-Maxx® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) SUSTIBLISTON LITERITY Insert, threaded steel (replacement inserts for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) (includes (1) left and (1) right threaded insert) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) Suspension pin retainer (4) Suspension pin set, front or rear corner (hardened steel), 4x85mm (1), 4x47mm (3), 4x33mm (2) (qty 4, #7740 required for complete set)
5032 5033 5034 5035 5036 5037 5029 5038 7765 7765 7765 7765 7765 7763 7763 7764	Oil, shock (30 wt, 350 cSt, 60cc) (silicone) Oil, shock (40 wt, 500 cSt, 60cc) (silicone) Oil, shock (50 wt, 600 cSt, 60cc) (silicone) Oil, shock (60 wt, 700 cSt, 60cc) (silicone) Oil, shock (70 wt, 900 cSt, 60cc) (silicone) Oil, shock (80 wt, 1,000 cSt, 60cc) (silicone) Oil, shock (80 wt, 1,000 cSt, 60cc) (silicone) Shock oil bottle (60cc) (for mixing shock oil) X Shock oil set (includes 20 wt, 30 wt, 40 wt, 50 wt, 60 wt, 70 wt, & 80 wt premium shock oils with spinning carousel rack) Silicone shock oil (30 wt), 60cc Spinning carousel rack SIDEKS (STX) A Body, GTX shock (aluminum, black-anodized) (1) Body, GTX shock (aluminum, pred-anodized) (1) Body, GTX shock (aluminum, orange-anodized) (1) R Body, GTX shock (aluminum, red-anodized) (1) R Body, GTX shock (aluminum, red-anodized) (1) R Body, GTX shock (hard-anodized, PTFE-coated aluminum) (1) Rebuild kit, GTX shocks (lower cartridge, assembled, pistons, piston nuts, bladders) (renews 2 shocks) Shaft, GTX shock, 110mm (assembled with rod ends & hollow balls) (steel, chrome finish) (2) T Shaft, GTX shock, TiN-coated (2) (assembled with rod ends and steel hollow balls) A Shock caps, aluminum (blue-anodized), GTX shocks (4)/ spacers (8) Shock caps, aluminum (green-anodized, PTFE-coated), GTX shocks (4)/ spacers (8)	5119 5116 7747 7746 7746X 7748X 7748G 7748R 7748R 7798 7797	Ball bearings, blue rubber sealed (10x15x4mm) (2) Ball bearings, blue rubber sealed (5x11x4mm) (2) Servo horn, steering/ linkage, steering (46mm, assembled with pivot balls) Steering bellcranks/ bellcrank support/servo saver/ servo saver spring/ draglink/ 3x20mm shoulder screws (2) Steering link, steel/ servo saver spring, heavy duty (use with #2085X metal gear servo) Toe links, molded composite, 173mm (158mm center to center) (black) (2) Toe links, X-Maxx® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Tol links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) SISTEMBER LINE LINE LINE LINE LINE LINE LINE LINE
5032 5033 5034 5035 5036 5037 5029 5038 7765 7765 7765 7765 7765 7763 7763 7764 7764	Oil, shock (30 wt, 350 cSt, 60cc) (silicone) Oil, shock (40 wt, 500 cSt, 60cc) (silicone) Oil, shock (50 wt, 600 cSt, 60cc) (silicone) Oil, shock (60 wt, 700 cSt, 60cc) (silicone) Oil, shock (70 wt, 900 cSt, 60cc) (silicone) Oil, shock (80 wt, 1,000 cSt, 60cc) (silicone) Oil, shock (80 wt, 1,000 cSt, 60cc) (silicone) Shock oil bottle (60cc) (for mixing shock oil) X Shock oil set (includes 20 wt, 30 wt, 40 wt, 50 wt, 60 wt, 70 wt, & 80 wt premium shock oils with spinning carousel rack) Silicone shock oil (30 wt), 60cc Spinning carousel rack SIDEKS (STX) A Body, GTX shock (aluminum, black-anodized) (1) Body, GTX shock (aluminum, pred-anodized) (1) Body, GTX shock (aluminum, orange-anodized) (1) R Body, GTX shock (aluminum, red-anodized) (1) R Body, GTX shock (aluminum, red-anodized) (1) R Body, GTX shock (hard-anodized, PTFE-coated aluminum) (1) Rebuild kit, GTX shocks (lower cartridge, assembled, pistons, piston nuts, bladders) (renews 2 shocks) Shaft, GTX shock, 110mm (assembled with rod ends & hollow balls) (steel, chrome finish) (2) T Shaft, GTX shock, TiN-coated (2) (assembled with rod ends and steel hollow balls) A Shock caps, aluminum (blue-anodized), GTX shocks (4)/ spacers (8) Shock caps, aluminum (green-anodized, PTFE-coated), GTX shocks (4)/ spacers (8)	5119 5116 7747 7746 7746X 7748X 7748G 7748R 7798 7798 7797	Ball bearings, blue rubber sealed (10x15x4mm) (2) Ball bearings, blue rubber sealed (5x11x4mm) (2) Servo horn, steering/ linkage, steering (46mm, assembled with pivot balls) Steering bellcranks/ bellcrank support/servo saver/ servo saver spring/ draglink/ 3x20mm shoulder screws (2) Steering link, steel/ servo saver spring, heavy duty (use with #2085X metal gear servo) Toe links, molded composite, 173mm (158mm center to center) (black) (2) Toe links, X-Maxx® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) SUSJOINS (DIL LINKS) INSTORM (1) LINKS (1) LINKS (1) LINKS (2) LINKS (2) LINKS (2) LINKS (3) LINKS
5032 5033 5034 5035 5036 5037 5029 5038 7765 7765 7765 7765 7765 7763 7763 7764 7764	Oil, shock (30 wt, 350 cSt, 60cc) (silicone) Oil, shock (40 wt, 500 cSt, 60cc) (silicone) Oil, shock (50 wt, 600 cSt, 60cc) (silicone) Oil, shock (60 wt, 700 cSt, 60cc) (silicone) Oil, shock (70 wt, 900 cSt, 60cc) (silicone) Oil, shock (80 wt, 1,000 cSt, 60cc) (silicone) Oil, shock (80 wt, 1,000 cSt, 60cc) (silicone) Shock oil bottle (60cc) (for mixing shock oil) X Shock oil set (includes 20 wt, 30 wt, 40 wt, 50 wt, 60 wt, 70 wt, & 80 wt premium shock oils with spinning carousel rack) Silicone shock oil (30 wt), 60cc Spinning carousel rack SIDELS [FIII] A Body, GTX shock (aluminum, blue-anodized) (1) Body, GTX shock (aluminum, green-anodized) (1) Body, GTX shock (aluminum, orange-anodized) (1) R Body, GTX shock (aluminum, red-anodized) (1) R Body, GTX shock (faluminum, red-anodized) (1) R Body, GTX shock (lower cartridge, assembled, pistons, piston nuts, bladders) (renews 2 shocks) Shaft, GTX shock, 110mm (assembled with rod ends & hollow balls) (steel, chrome finish) (2) T Shaft, GTX shock, TiN-coated (2) (assembled with rod ends and steel hollow balls) A Shock caps, aluminum (blue-anodized), GTX shocks (4)/ spacers (8) Shock caps, aluminum (green-anodized), GTX shocks (4)/ spacers (8) Shock caps, aluminum (hard-anodized, PTFE-coated), GTX shocks (4)/ spacers (8) Shock caps, aluminum (red-anodized, GTX shocks (4)/ spacers (8) Shock caps, aluminum (red-anodized, GTX shocks (4)/ spacers (8)	5119 5116 7747 7746 7746X 7748X 7748X 7748G 7748R 7798 7797 7743 7740 7742	Ball bearings, blue rubber sealed (10x15x4mm) (2) Ball bearings, blue rubber sealed (5x11x4mm) (2) Servo horn, steering/ linkage, steering (46mm, assembled with pivot balls) Steering bellcranks/ bellcrank support/servo saver/ servo saver spring/ draglink/ 3x20mm shoulder screws (2) Steering link, steel/ servo saver spring, heavy duty (use with #2085X metal gear servo) Toe links, molded composite, 173mm (158mm center to center) (black) (2) Toe links, X-Maxx® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx®, TVABES, 8542T, 8542X) (includes (1) left and (1) right threaded insert) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) Suspension pin retainer (4) Suspension pin set, front or rear corner (hardened steel), 4x85mm (1), 4x47mm (3), 4x33mm (2) (qty 4, #7740 required for complete set) Suspension pin set, shock mount (front or rear, hardened steel), 4x25mm (2), 4x38mm (2)
5032 5033 5034 5035 5036 5037 5029 5038 1667 5038 7765 7765 7765 7765 7765 7764 7764 7764	Oil, shock (30 wt, 350 cSt, 60cc) (silicone) Oil, shock (40 wt, 500 cSt, 60cc) (silicone) Oil, shock (50 wt, 600 cSt, 60cc) (silicone) Oil, shock (60 wt, 700 cSt, 60cc) (silicone) Oil, shock (70 wt, 900 cSt, 60cc) (silicone) Oil, shock (80 wt, 1,000 cSt, 60cc) (silicone) Oil, shock (80 wt, 1,000 cSt, 60cc) (silicone) Shock oil bottle (60cc) (for mixing shock oil) X Shock oil set (includes 20 wt, 30 wt, 40 wt, 50 wt, 60 wt, 70 wt, & 80 wt premium shock oils with spinning carousel rack) Silicone shock oil (30 wt), 60cc Spinning carousel rack SIDELS [FIII] A Body, GTX shock (aluminum, black-anodized) (1) Body, GTX shock (aluminum, green-anodized) (1) Body, GTX shock (aluminum, orange-anodized) (1) Rody, GTX shock (aluminum, red-anodized) (1) Rody, GTX shock (faluminum, red-anodized) (1) Rody, GTX shock (hard-anodized, PTFE-coated aluminum) (1) Rebuild kit, GTX shocks (lower cartridge, assembled, pistons, piston nuts, bladders) (renews 2 shocks) Shaft, GTX shock, 110mm (assembled with rod ends & hollow balls) (steel, chrome finish) (2) T Shaft, GTX shock, TiN-coated (2) (assembled with rod ends and steel hollow balls) A Shock caps, aluminum (blue-anodized), GTX shocks (4)/ spacers (8) Shock caps, aluminum (green-anodized), GTX shocks (4)/ spacers (8) Shock caps, aluminum (hard-anodized, PTFE-coated), GTX shocks (4)/ spacers (8) Shock caps, aluminum (red-anodized), GTX shocks (4)/ spacers (8) Shock caps, aluminum (red-anodized), GTX shocks (4)/ spacers (8)	5119 5116 7747 7746 7746X 7748 7748X 7748G 7748R 7798 7797 7743 7740 7742 7741	Ball bearings, blue rubber sealed (10x15x4mm) (2) Ball bearings, blue rubber sealed (5x11x4mm) (2) Servo horn, steering/ linkage, steering (46mm, assembled with pivot balls) Steering bellcranks/ bellcrank support/servo saver/ servo saver spring/ draglink/ 3x20mm shoulder screws (2) Steering link, steel/ servo saver spring, heavy duty (use with #2085X metal gear servo) Toe links, molded composite, 173mm (158mm center to center) (black) (2) Toe links, X-Maxx® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) SISTEMON LINKED LI
5032 5033 5034 5035 5036 5037 5029 5038 1667 5038 7765 7765 7765 7765 7765 7764 7764 7764	Oil, shock (30 wt, 350 cSt, 60cc) (silicone) Oil, shock (40 wt, 500 cSt, 60cc) (silicone) Oil, shock (50 wt, 600 cSt, 60cc) (silicone) Oil, shock (60 wt, 700 cSt, 60cc) (silicone) Oil, shock (70 wt, 900 cSt, 60cc) (silicone) Oil, shock (80 wt, 1,000 cSt, 60cc) (silicone) Oil, shock (80 wt, 1,000 cSt, 60cc) (silicone) Shock oil bottle (60cc) (for mixing shock oil) X Shock oil set (includes 20 wt, 30 wt, 40 wt, 50 wt, 60 wt, 70 wt, & 80 wt premium shock oils with spinning carousel rack) Silicone shock oil (30 wt), 60cc Spinning carousel rack SIDELS (FIN) A Body, GTX shock (aluminum, black-anodized) (1) Body, GTX shock (aluminum, preen-anodized) (1) Body, GTX shock (aluminum, orange-anodized) (1) R Body, GTX shock (aluminum, red-anodized) (1) R Body, GTX shock (fard-anodized, PTFE-coated aluminum) (1) Rebuild kit, GTX shocks (lower cartridge, assembled, pistons, piston nuts, bladders) (renews 2 shocks) Shaft, GTX shock, 110mm (assembled with rod ends & hollow balls) (steel, chrome finish) (2) Shaft, GTX shock, TiN-coated (2) (assembled with rod ends and steel hollow balls) A Shock caps, aluminum (blue-anodized), GTX shocks (4)/ spacers (8) Shock caps, aluminum (green-anodized), GTX shocks (4)/ spacers (8) Shock caps, aluminum (red-anodized), GTX shocks (4)/ spacers (8) Shock caps, GTX shocks/ spring perch/ adjusters/ 2.5x14mm CS (2) (for 2 shocks)	5119 5116 7747 7746 7746X 7748 7748X 7748G 7748R 7798 7797 7743 7740 7742 7741	Ball bearings, blue rubber sealed (10x15x4mm) (2) Ball bearings, blue rubber sealed (5x11x4mm) (2) Servo horn, steering/ linkage, steering (46mm, assembled with pivot balls) Steering bellcranks/ bellcrank support/servo saver/ servo saver spring/ draglink/ 3x20mm shoulder screws (2) Steering link, steel/ servo saver spring, heavy duty (use with #2085X metal gear servo) Toe links, molded composite, 173mm (158mm center to center) (black) (2) Toe links, X-Maxx® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) Suspension pin retainer (4) Suspension pin set, front or rear corner (hardened steel), 4x85mm (1), 4x47mm (3), 4x33mm (2) (qty 4, #7740 required for complete set) Suspension pins, 4x85mm (1), 4x25mm (2), 4x38mm (2) Suspension pins, 4x85mm (hardened steel) (2) Toe links, molded composite, 173mm (158mm center to center)
5032 5033 5034 5035 5036 5037 5029 5038 1667 5038 7765 7765 7765 7765 7763 7764 7764 7764	Oil, shock (30 wt, 350 cSt, 60cc) (silicone) Oil, shock (40 wt, 500 cSt, 60cc) (silicone) Oil, shock (50 wt, 600 cSt, 60cc) (silicone) Oil, shock (60 wt, 700 cSt, 60cc) (silicone) Oil, shock (70 wt, 900 cSt, 60cc) (silicone) Oil, shock (80 wt, 1,000 cSt, 60cc) (silicone) Oil, shock (80 wt, 1,000 cSt, 60cc) (silicone) Shock oil bottle (60cc) (for mixing shock oil) X Shock oil set (includes 20 wt, 30 wt, 40 wt, 50 wt, 60 wt, 70 wt, & 80 wt premium shock oils with spinning carousel rack) Silicone shock oil (30 wt), 60cc Spinning carousel rack SIDELS (FIN) A Body, GTX shock (aluminum, black-anodized) (1) Body, GTX shock (aluminum, preen-anodized) (1) Body, GTX shock (aluminum, orange-anodized) (1) R Body, GTX shock (aluminum, red-anodized) (1) R Body, GTX shock (fard-anodized, PTFE-coated aluminum) (1) Rebuild kit, GTX shocks (lower cartridge, assembled, pistons, piston nuts, bladders) (renews 2 shocks) Shaft, GTX shock, 110mm (assembled with rod ends & hollow balls) (steel, chrome finish) (2) Shaft, GTX shock, TiN-coated (2) (assembled with rod ends and steel hollow balls) A Shock caps, aluminum (blue-anodized), GTX shocks (4)/ spacers (8) Shock caps, aluminum (green-anodized), GTX shocks (4)/ spacers (8) Shock caps, aluminum (red-anodized), GTX shocks (4)/ spacers (8) Shock caps, GTX shocks/ spring perch/ adjusters/ 2.5x14mm CS (2) (for 2 shocks)	5119 5116 7747 7746 7746X 7748X 7748G 7748R 7798 7797 7743 7740 7742 7741 7748	Ball bearings, blue rubber sealed (10x15x4mm) (2) Ball bearings, blue rubber sealed (5x11x4mm) (2) Servo horn, steering/ linkage, steering (46mm, assembled with pivot balls) Steering bellcranks/ bellcrank support/servo saver/ servo saver spring/ draglink/ 3x20mm shoulder screws (2) Steering link, steel/ servo saver spring, heavy duty (use with #2085X metal gear servo) Toe links, molded composite, 173mm (158mm center to center) (black) (2) Toe links, X-Maxx® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) Suspension pin retainer (4) Suspension pin set, front or rear corner (hardened steel), 4x85mm (1), 4x47mm (3), 4x33mm (2) (qty 4, #7740 required for complete set) Suspension pins, 4x85mm (hardened steel) (2) Toe links, molded composite, 173mm (158mm center to center) (black) (2)
5032 5033 5034 5035 5036 5037 5029 5038 1667 5038 7765 7765 7765 7765 7763 7764 7764 7764	Oil, shock (30 wt, 350 cSt, 60cc) (silicone) Oil, shock (40 wt, 500 cSt, 60cc) (silicone) Oil, shock (50 wt, 600 cSt, 60cc) (silicone) Oil, shock (50 wt, 600 cSt, 60cc) (silicone) Oil, shock (70 wt, 900 cSt, 60cc) (silicone) Oil, shock (80 wt, 7,000 cSt, 60cc) (silicone) Oil, shock (80 wt, 1,000 cSt, 60cc) (silicone) Shock oil bottle (60cc) (for mixing shock oil) X Shock oil set (includes 20 wt, 30 wt, 40 wt, 50 wt, 60 wt, 70 wt, & 80 wt premium shock oils with spinning carousel rack) Silicone shock oil (30 wt), 60cc Spinning carousel rack SIDCES [CILI] A Body, GTX shock (aluminum, blue-anodized) (1) Body, GTX shock (aluminum, preen-anodized) (1) Body, GTX shock (aluminum, orange-anodized) (1) Body, GTX shock (aluminum, red-anodized) (1) Rebuild kit, GTX shock (lower cartridge, assembled, pistons, piston nuts, bladders) (renews 2 shocks) Shaft, GTX shock, 110mm (assembled with rod ends & hollow balls) (steel, chrome finish) (2) T Shaft, GTX shock, TiN-coated (2) (assembled with rod ends and steel hollow balls) A Shock caps, aluminum (blue-anodized), GTX shocks (4)/ spacers (8) G Shock caps, aluminum (green-anodized), GTX shocks (4)/ spacers (8) R Shock caps, aluminum (hard-anodized, PTFE-coated), GTX shocks (4)/ spacers (8) R Shock caps, aluminum (red-anodized), GTX shocks (4)/ spacers (8) Shock caps, GTX shocks/ spring perch/ adjusters/ 2.5x14mm CS (2) (for 2 shocks) A Shocks, GTX, aluminum (black-anodized) (fully assembled w/o springs) (2)	5119 5116 7747 7746 7746X 7748X 7748G 7748R 7798 7797 7743 7740 7742 7741 7748	Ball bearings, blue rubber sealed (10x15x4mm) (2) Ball bearings, blue rubber sealed (5x11x4mm) (2) Servo horn, steering/ linkage, steering (46mm, assembled with pivot balls) Steering bellcranks/ bellcrank support/servo saver/ servo saver spring/ draglink/ 3x20mm shoulder screws (2) Steering link, steel/ servo saver spring, heavy duty (use with #2085X metal gear servo) Toe links, molded composite, 173mm (158mm center to center) (black) (2) Toe links, X-Maxx® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) SUSJUBICION LITERION (1) Insert, threaded steel (replacement inserts for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) Suspension pin retainer (4) Suspension pin retainer (4) Suspension pin set, front or rear corner (hardened steel), 4x85mm (1), 4x47mm (3), 4x33mm (2) (qty 4, #7740 required for complete set) Suspension pin set, shock mount (front or rear, hardened steel), 4x25mm (2), 4x38mm (2) Suspension pins, 4x85mm (hardened steel) (2) Toe links, molded composite, 173mm (158mm center to center) (black) (2) Toe links, X-Maxx® (TUBES blue-anodized, 7075-T6 aluminum,
5032 5033 5034 5035 5036 5037 5029 5038 1667 5038 7765 7765 7765 7765 7763 7764 7764 7764 7764 7764 7761	Oil, shock (30 wt, 350 cSt, 60cc) (silicone) Oil, shock (40 wt, 500 cSt, 60cc) (silicone) Oil, shock (50 wt, 600 cSt, 60cc) (silicone) Oil, shock (60 wt, 700 cSt, 60cc) (silicone) Oil, shock (70 wt, 900 cSt, 60cc) (silicone) Oil, shock (80 wt, 1,000 cSt, 60cc) (silicone) Oil, shock (80 wt, 1,000 cSt, 60cc) (silicone) Shock oil bottle (60cc) (for mixing shock oil) Shock oil set (includes 20 wt, 30 wt, 40 wt, 50 wt, 60 wt, 70 wt, & 80 wt premium shock oils with spinning carousel rack) Silicone shock oil (30 wt), 60cc Spinning carousel rack SIDCES (GTI) A Body, GTX shock (aluminum, black-anodized) (1) Body, GTX shock (aluminum, blue-anodized) (1) Body, GTX shock (aluminum, orange-anodized) (1) Body, GTX shock (aluminum, red-anodized) (1) Body, GTX shock (laluminum, red-anodized) (1) Rebuild kit, GTX shocks (lower cartridge, assembled, pistons, piston nuts, bladders) (renews 2 shocks) Shaft, GTX shock, 110mm (assembled with rod ends & hollow balls) (steel, chrome finish) (2) T Shaft, GTX shock, TiN-coated (2) (assembled with rod ends and steel hollow balls) A Shock caps, aluminum (blue-anodized), GTX shocks (4)/ spacers (8) Shock caps, aluminum (red-anodized), GTX shocks (4)/ spacers (8) Shock caps, aluminum (red-anodized), GTX shocks (4)/ spacers (8) Shock caps, GTX shocks/ spring perch/ adjusters/ 2.5x14mm CS (2) (for 2 shocks) A Shocks, GTX, aluminum (blue-anodized) (fully assembled w/o springs) (2) Shocks, GTX, aluminum (blue-anodized) (fully assembled w/o springs) (2)	5119 5116 7747 7746 7746X 7748X 7748G 7748R 7798 7797 7743 7740 7742 7741 7748	Ball bearings, blue rubber sealed (10x15x4mm) (2) Ball bearings, blue rubber sealed (5x11x4mm) (2) Servo horn, steering/ linkage, steering (46mm, assembled with pivot balls) Steering bellcranks/ bellcrank support/servo saver/ servo saver spring/ draglink/ 3x20mm shoulder screws (2) Steering link, steel/ servo saver spring, heavy duty (use with #2085X metal gear servo) Toe links, molded composite, 173mm (158mm center to center) (black) (2) Toe links, X-Maxx® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) SUSPENSION LINKERS (10 ends, 40)/ aluminum wrench, 10mm (1) SUSPENSION LINKERS (11 ends)/ aluminum wrench, 10mm (1) SUSPENSION LINKERS (12 ends)/ aluminum wrench, 10mm (1) SUSPENSION LINKERS (13 ends)/ aluminum wrench, 10mm (1) SUSPENSION LINKERS (14 ends)/ aluminum wrench, 10mm (1) SUSPENSION pin set, front or rear corner (hardened steel), 4x85mm (1), 4x47mm (3), 4x33mm (2) (qty 4, #7740 required for complete set) Suspension pin set, shock mount (front or rear, hardened steel), 4x25mm (2), 4x38mm (2) Suspension pins, 4x85mm (hardened steel) (2) Toe links, X-Maxx® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES plee-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1)
5032 5033 5034 5035 5036 5037 5029 5038 7765 7765 7765 7765 7763 7764 7764 7764 7764	Oil, shock (30 wt, 350 cSt, 60cc) (silicone) Oil, shock (40 wt, 500 cSt, 60cc) (silicone) Oil, shock (50 wt, 600 cSt, 60cc) (silicone) Oil, shock (60 wt, 700 cSt, 60cc) (silicone) Oil, shock (70 wt, 900 cSt, 60cc) (silicone) Oil, shock (80 wt, 1,000 cSt, 60cc) (silicone) Oil, shock (80 wt, 1,000 cSt, 60cc) (silicone) Shock oil bottle (60cc) (for mixing shock oil) Shock oil set (includes 20 wt, 30 wt, 40 wt, 50 wt, 60 wt, 70 wt, & 80 wt premium shock oils with spinning carousel rack) Silicone shock oil (30 wt), 60cc Spinning carousel rack SIDCES (GTI) A Body, GTX shock (aluminum, black-anodized) (1) Body, GTX shock (aluminum, blue-anodized) (1) Body, GTX shock (aluminum, orange-anodized) (1) Body, GTX shock (aluminum, red-anodized) (1) Body, GTX shock (laluminum, red-anodized) (1) Rebuild kit, GTX shocks (lower cartridge, assembled, pistons, piston nuts, bladders) (renews 2 shocks) Shaft, GTX shock, 110mm (assembled with rod ends & hollow balls) (steel, chrome finish) (2) T Shaft, GTX shock, TiN-coated (2) (assembled with rod ends and steel hollow balls) A Shock caps, aluminum (blue-anodized), GTX shocks (4)/ spacers (8) Shock caps, aluminum (red-anodized), GTX shocks (4)/ spacers (8) Shock caps, aluminum (red-anodized), GTX shocks (4)/ spacers (8) Shock caps, GTX shocks/ spring perch/ adjusters/ 2.5x14mm CS (2) (for 2 shocks) A Shocks, GTX, aluminum (blue-anodized) (fully assembled w/o springs) (2) Shocks, GTX, aluminum (blue-anodized) (fully assembled w/o springs) (2)	5119 5116 7747 7746 7746X 7748 7748X 7748G 7748R 7798 7797 7743 7740 7742 7741 7748 7748X	Ball bearings, blue rubber sealed (10x15x4mm) (2) Ball bearings, blue rubber sealed (5x11x4mm) (2) Servo horn, steering/ linkage, steering (46mm, assembled with pivot balls) Steering bellcranks/ bellcrank support/servo saver/ servo saver spring/ draglink/ 3x20mm shoulder screws (2) Steering link, steel/ servo saver spring, heavy duty (use with #2085X metal gear servo) Toe links, molded composite, 173mm (158mm center to center) (black) (2) Toe links, X-Maxx® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) SISICISION (11) Integral Insert, threaded steel (replacement inserts for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) (includes (1) left and (1) right threaded insert) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) Suspension pin retainer (4) Suspension pin set, front or rear corner (hardened steel), 4x85mm (1), 4x47mm (3), 4x33mm (2) (qty 4, #7740 required for complete set) Suspension pin set, shock mount (front or rear, hardened steel), 4x25mm (2), 4x38mm (2) Suspension pins, 4x85mm (hardened steel) (2) Toe links, molded composite, 173mm (158mm center to center) (black) (2) Toe links, X-Maxx® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1)

	71		····· (
7748R	Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1)	2748R	Tool set (includes 1.5mm hex wrench / 2.0mm hex wrench / 2.5mm hex wrench/ 4-way wrench/ 8mm & 4mm wrench/ U-joint wrench)
	Team Traxxas Items	3415	Tool set with pouch (includes 1.5mm, 2.0mm, 2.5mm, 3.0mm,
2514			3.5mm, 4mm drivers/ 4mm, 5mm, 5.5mm, 7mm and 8mm nut
2514 9950	Decal sheet, racing sponsors Official Team Traxxas® racing decal set (flag logo/ 6-color)		drivers/ 2mm, 4mm, and 5mm slotted screwdrivers/ #00 Phillips,
9909	Traxxas® racing banner, red & black (3x7 feet)		#0 Phillips, and #1 Phillips screwdrivers/ 4mm and 8mm wrench/ driver handle
3303	Tires & Wheels	5480X	Wheel wrench, splined, 17mm
		0.10074	Turnbuckles & Threaded Rods
7772A	Tires & wheels, assembled, glued (X-Maxx® black chrome wheels, Maxx® AT tires, foam inserts) (left & right) (2)	7700	
7774A	Tires & wheels, assembled, glued (X-Maxx® black chrome	7798	Insert, threaded steel (replacement inserts for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) (includes (1) left and (1)
111-11	wheels, Sledgehammer® tires, foam inserts) (left & right) (2)		right threaded insert)
7772X	Tires & wheels, assembled, glued (X-Maxx® black wheels, Maxx® AT	7797	Rod ends (4) (assembled with steel pivot balls) (replacement
	tires, foam inserts) (left & right) (2)		ends for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X)
7773	Tires & wheels, assembled, glued (X-Maxx® black wheels,	7748	Toe links, molded composite, 173mm (158mm center to center)
	paddle tires, foam inserts) (left & right) (2)		(black) (2)
7772G	Tires & wheels, assembled, glued (X-Maxx® green wheels, Maxx® AT tires, foam inserts) (left & right) (2)	7748X	Toe links, X-Maxx® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with
7774G	Tires & wheels, assembled, glued (X-Maxx® green wheels,		stronger than titalindin) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1)
11140	Sledgehammer® tires, foam inserts) (left & right) (2)	7748G	Toe links, X-Maxx® (TUBES green-anodized, 7075-T6 aluminum,
7772T	Tires & wheels, assembled, glued (X-Maxx® orange wheels,		stronger than titanium) (157mm) (2)/ rod ends, assembled with
	Maxx® AT tires, foam inserts) (left & right) (2)		steel hollow balls (4)/ aluminum wrench, 10mm (1)
7774T	Tires & wheels, assembled, glued (X-Maxx® orange wheels,	7748R	Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum,
7770D	Sledgehammer® tires, foam inserts) (left & right) (2)		stronger than titanium) (157mm) (2)/ rod ends, assembled with
7772R	Tires & wheels, assembled, glued (X-Maxx® satin chrome wheels, Maxx® AT tires, foam inserts) (left & right) (2)		steel hollow balls (4)/ aluminum wrench, 10mm (1)
7770X	Tires, Maxx® AT (left & right) (2)/ foam inserts (2)		WideMaxx® Suspension Kit
7757	Wheel hex clips (6)	7896	Driveshaft, steel constant velocity (shaft only, 190.3mm) (1) (for
7756	Wheel hubs, hex (2)/ hex clips (2)	7004	use with #7895 X-Maxx® WideMaxx® suspension kit)
7756X	Wheel hubs, hex, aluminum (blue-anodized) (4)	7894	Suspension arm, lower, black (1) (left, front or rear) (for use with #7895 X-Maxx® WideMaxx® suspension kit)
7756G	Wheel hubs, hex, aluminum (green-anodized) (4)	7893	Suspension arm, lower, black (1) (right, front or rear) (for use
7756R	Wheel hubs, hex, aluminum (red-anodized) (4)	1000	with #7895 X-Maxx® WideMaxx® suspension kit)
7758A	Wheel nuts, splined, 17mm, serrated (black-anodized) (4)	7894X	Suspension arm, lower, blue (1) (left, front or rear) (for use with
7758	Wheel nuts, splined, 17mm, serrated (blue-anodized) (4)		#7895 X-Maxx® WideMaxx® suspension kit)
7758G 7758T	Wheel nuts, splined, 17mm, serrated (green-anodized) (4) Wheel nuts, splined, 17mm, serrated (orange-anodized) (4)	7893X	Suspension arm, lower, blue (1) (right, front or rear) (for use with
7758R	Wheel nuts, splined, 17mm, serrated (transperantolized) (4)	70040	#7895 X-Maxx® WideMaxx® suspension kit)
5480X	Wheel wrench, splined, 17mm	7894G	Suspension arm, lower, green (1) (left, front or rear) (for use with #7895 X-Maxx® WideMaxx® suspension kit)
7771	Wheels, X-Maxx®, black (left & right)	7893G	Suspension arm, lower, green (1) (right, front or rear) (for use
	Transmission Components		with #7895 X-Maxx® WideMaxx® suspension kit)
7796	Center drive, torque-biasing (assembled)/ 17x26x5 ball bearings (2)	7894T	Suspension arm, lower, orange (1) (left, front or rear) (for use
1190	(requires #7727X bulkheads)		with #7895 X-Maxx® WideMaxx® suspension kit)
7787	Covers, gear (3)	7893T	Suspension arm, lower, orange (1) (right, front or rear) (for use
7785X	Input gear, transmission, 20-tooth/ 2.5x12mm pin	7894R	with #7895 X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, red (1) (left, front or rear) (for use with
7786X	Input shaft, transmission (cush drive)	703410	#7895 X-Maxx® WideMaxx® suspension kit)
5040	Oil, differential (20M wt) (standard)	7893R	Suspension arm, lower, red (1) (right, front or rear) (for use with
7784X	Output gear, 51-tooth, metal (requires #7785X input gear)		#7895 X-Maxx® WideMaxx® suspension kit)
	Traxxas Tools	7892	Suspension arms, upper, black (left or right, front or rear) (2) (for
3433X	Body reamer (aluminum handle)	7002V	use with #7895 X-Maxx® WideMaxx® suspension kit)
3433	Body reamer (plastic handle)	7892X	Suspension arms, upper, blue (left or right, front or rear) (2) (for use with #7895 X-Maxx® WideMaxx® suspension kit)
3436	Cap, body reamer	7892G	Suspension arms, upper, green (left or right, front or rear) (2) (for
3432	Scissors, curved tip		use with #7895 X-Maxx® WideMaxx® suspension kit)
3431	Scissors, straight tip	7892T	Suspension arms, upper, orange (left or right, front or rear) (2)
8712	Speed Bit Essentials Set, hex and nut driver, 7-piece, includes premium handle (medium), travel pouch, hex drivers (straight:		(for use with #7895 X-Maxx® WideMaxx® suspension kit)
	1.5mm, 2.0mm, 2.5mm) and nut drivers (5.0mm, 5.5mm, 7.0mm,	7892R	Suspension arms, upper, red (left or right, front or rear) (2) (for use with #7895 X-Maxx® WideMaxx® suspension kit)
	and 8.0mm), 1/4" drive	7895	Suspension kit, X-Maxx® WideMaxx®, black (includes front &
8721	Speed bit handle, medium (one piece)	7000	rear suspension arms, front toe links, driveshafts, shock
8720	Speed bit handle, premium, large (rubber overmold)		springs)
8722	Speed bit handle, premium, medium (rubber overmold)	7895X	Suspension kit, X-Maxx® WideMaxx®, blue (includes front & rear
8710	Speed Bit Master Set, hex and nut driver, 13-piece, includes premium handle (medium), travel pouch, hex drivers (straight:		suspension arms, front toe links, driveshafts, shock springs)
	1.5mm, 2.0mm, 2.5mm, 3.0mm), (ball-end: 2.0mm, 2.5mm,	7895G	Suspension kit, X-Maxx® WideMaxx®, green (includes front & rear suspension arms, front toe links, driveshafts, shock
	3.0mm), and nut drivers (4.00mm, 4.50mm, 5.00mm, 5.50mm,		springs)
	7.00mm, 8.00mm),	7895T	Suspension kit, X-Maxx® WideMaxx®, orange (includes front &
8711	Speed Bit Master Set, hex driver, 7-piece straight and ball end,		rear suspension arms, front toe links, driveshafts, shock
	includes premium handle (medium), travel pouch, hex drivers (straight: 1.5mm, 2.0mm, 2.5mm, 3.0mm) (ball end: 2.0mm,		springs)
	2.5mm, 3.0mm), 1/4" drive	7895R	Suspension kit, X-Maxx® WideMaxx®, red (includes front & rear
8719	Speed Bit Master Set, nut driver, 6-piece, includes premium	7897	suspension arms, front toe links, driveshafts, shock springs) Toe links, 202.5mm (187.5mm center to center) (black) (2) (for
	handle (medium), travel pouch, and nut drivers (4.0mm, 4.5mm,	1091	use with #7895 X-Maxx® WideMaxx® suspension kit)
	5.0mm, 5.5mm, 7.0mm, 8.0mm), 1/4" drive	7897A	Toe links, front (TUBES black-anodized, 6061-T6 aluminum) (2)
8716	Speed Bit Set, hex driver, 2-piece ball-end (2.0mm, 2.5mm), 1/4"		(for use with #7895 X-Maxx® WideMaxx® suspension kit)
8716X	drive Speed Bit Set, hex driver, 3-piece ball-end (2.0mm, 2.5mm,	7897X	Toe links, front (TUBES blue-anodized, 6061-T6 aluminum) (2)
01 108	3.0mm), 1/4" drive	=	(for use with #7895 X-Maxx® WideMaxx® suspension kit)
8715	Speed Bit Set, hex driver, 3-piece straight (1.5mm, 2.0mm,	7897G	Toe links, front (TUBES green-anodized, 6061-T6 aluminum) (2)
	2.5mm), 1/4" drive	7897R	(for use with #7895 X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES red-anodized, 6061-T6 aluminum) (2) (for
8715X	Speed Bit Set, hex driver, 4-piece straight (1.5mm, 2.0mm,	. 55.11	use with #7895 X-Maxx® WideMaxx® suspension kit)
	2.5mm, 3.0mm), 1/4" drive		·